

March 2018

PRODUCT DATA SHEET

Product	Quick Drying Aluminium Paint
Type	Waterborne acrylic resin emulsion. Available as gloss finish only. Suitable for interior and exterior use.
Intended Use	Ideal for use on wood, metal and plaster.
Special Features	Heat resistant up to 105°C.
Preparation	Surface should clean and free from grease and wax. If the metal is rusty, remove loose rust with a wire brush and treat with Rustin's Rust Remover .
Application	Apply evenly with a synthetic bristle brush.
Coats	Two coats may be sufficient but three coats are recommended for exterior surface.
Drying Time	Touch dry in 30 minutes.
Re-coating Time	Can be recoated after 2 hours depending on temperature and humidity.
Application Temp.	Ideally 10-25 °C. Do not use in conditions of high humidity and very low temperature.
Coverage	Approximately 12 sq. metres/ Coat per litre
Maintenance	Clean surfaces with a mild detergent solution. Worn areas may be re-coated once cleaned and lightly sanded to provide a key.
Compatibility	Not suitable for use on wood burning stoves or on surfaces which are in direct contact with a naked flame. If being used on metal surfaces for decorative purposes only, the metal can be applied with Rustin's Red Oxide Metal Primer before coating.
Settlement	Stir thoroughly before use.
Shelf-life/Storage	Many years if stored in original, tightly closed container. Store in cool and dry place.
Hazards	Harmful if swallowed. Keep out of reach of children. Rinse splashes from skin and eyes with plenty of water. A full health & safety data sheet is available upon request or at www.rustins.co.uk
Clean-Up	Use water whilst still wet. If dried on, clean equipment and brushes with Rustin's Brush Restorer .
Sizes	250ml, 500ml.