

March 2018

PRODUCT DATA SHEET

Product	Damp Seal
Type	A quick drying interior high performance solvent based paint based on polyester
Intended Use	For covering damp walls and ceilings, water stains and most household stains
Special Features	Quick drying and can be over coated with gloss or emulsion paint as well as wall paper. It does not cure damp but allows trapped moisture to escape. Not for exterior use.
Preparation	The surface must be clean and free from dust, loose paint and fungal growth or solid matter likely to interfere with the penetration of the sealer
Application	Stir well before use and apply 2 liberal coats.
Coats	Apply 2 coats and brush out approx. 30 cms beyond affected area.
Drying Time	1-2 hrs.
Re-coating Time	2 hrs between coats in warm conditions. Allow 2 hrs before applying a top coat or wall paper.
Application Temp.	Ideally 15-25 C. Do not use below 10 C or in conditions of high humidity.
Coverage	7 square metres per litre depending on absorbency of surface being treated.
Maintenance	N/A
Compatibility	Can be over coated with most oil based and water based paints.
Settlement	STIR WELL BEFORE USE.
Shelf-life/Storage	A very long time if stored in a cool dry place with the lid firmly secured. Do not store below 10 C.
Hazards	Flammable. Repeated exposure may cause skin dryness or cracking. Keep product out of reach of children. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear suitable protective clothing and gloves. Use only in well ventilated areas. For further information go to www.rustins.co.uk
Clean-Up	Remove as much product as possible from the brush and clean with Rustins Xylene Thinners or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.
Sizes	250ml 500ml 1Lt