

PRODUCT DATA SHEET

Product	Danish Oil
Type	Rustins Danish Oil is a blend of oils, resins and driers, formulated to produce an attractive and durable finish. The finish is Satin. For a gloss finish, use Rustins Teak Oil .
Intended Use	For all interior bare wood and joinery. Before use on veneered doors and timber refer to the furniture manufactures instructions as some coating products are not suitable for this application.
Special Features	Brings out the natural beauty of wood and veneered surfaces, gives a natural open-grained low lustre finish. Easy to maintain. Conforms to Safety of Toys Regulations BS EN 71 Part 3 1995. Conforms to the contact with Food Regulations.
Preparation	The bare wood must be clean, smooth, dry and free from wax, dust and contaminants. Remove wax by scrubbing with white spirit or Rustins Surface Cleaner and a scouring pad, then wipe away whilst still wet with clean rags. Existing paint and varnishes should be removed with Rustins Strypit Paint and Varnish Stripper . Bare wood may be dyed before coating with Rustin Wood Dye . Do not apply Rustins Knotting .
Application	Apply liberally with a clean rag or brush and wipe off the surplus oil after a few minutes. Nibs may be removed from the final coat by applying oil with a scouring pad, rubbing in the direction of the grain, then wiping away the surplus with clean rags or paper kitchen towels.
Coats	3 coats should be applied to bare wood.
Drying Time	4-6 hours depending on temperature and humidity.
Re-coating Time	Re-coat once the previous coat is dry.
Application Temp.	Ideally 15-25°C, do not apply below 5°C.
Coverage	Approximately 14sq.m per litre per coat depending on the absorbency of the wood.
Maintenance	Periodic re-oiling is required. Clean surfaces before re-oiling using White Spirit.
Compatibility	Danish Oil may be used over the following Rustins products. Wood Dye, Grainfiller and Woodfiller . The Rustins Wood Dye may also be added to Danish Oil. Do not exceed 30%. Rustins Polyurethane Varnish may be applied over Rustins Danish Oil at any time and the product can also be used as a wood primer before applying undercoat. The surface must be clean before varnishing.
Settlement	STIR WELL BEFORE USE or product will dry to a gloss finish.
Shelf-life/Storage	Many years if stored in original, tightly closed container in normal cool, dry conditions. Hazards. It is recommended that the oil is transferred to a smaller container as it is used up to minimise the airspace over the oil as this can cause the formation of a solid gel.
Hazards	Flammable. Avoid contact with eyes and skin. Use in a well ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking. Keep container tightly closed. A full safety data sheet is available upon request or on Rustins Web Site. Important: Rags used for oiling should be laid out flat to dry; otherwise they may catch fire due to

	spontaneous combustion.
Clean-Up	Clean brushes with White Spirit or Rustins Brush Cleaner whilst still wet. If dried on, clean brushes with Rustins Brush Restorer. Dried spills on surface should be removed with Rustins Strypit Paint and Varnish Remover.
Sizes	250ml 500ml 1litre 2.5Litre 5litre 25 litre