

Rustins Decking Cleaner is based on a blend of special cleaning agents to remove the dirt, algae, mildew and grease. Formulated to clean old and new decks. It can also be used to clean cladding, fences, window frames and any other exterior woodwork.

Preparation

All loose dirt, grease, mildew and mould should be removed using a stiff garden broom.

Application

Shake well before use. Apply Rustins Decking Cleaner with a watering can, sprayer or a brush. After 10 minutes, the surface should be scrubbed with a stiff garden broom. After a further 30 minutes, rinse the surface with clean water using a stiff broom or garden hose. Repeat the process as necessary until the deck is clean. Maintenance: Repeat the application of Rustins Decking Cleaner, when necessary.

Drying Time

Allow a minimum of 24 hours for the surface to dry thoroughly before applying Rustins Decking Stain & Seal or Rustins Decking Oil.

Coverage

This container will cover approximately 20-25 sq. metres of decking.

Cleaning

All equipment should be cleaned with plenty of water.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

May cause an allergic skin reaction. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wash contaminated clothing before reuse. Dispose of contents/ container to hazardous or special waste collection point.

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Tel: +44 (0)20 8450 4666

WARNING



Other products in the Rustins' Garden Range



Decking Oil

A hard wearing water-resistant oil that retains the colour of the decking. Contains Ultra Violet light inhibitors, plus biocide which protects the oil against mould and algae growth.



Textured Decking Oil

Rated as 'low slip potential' according to BS7976, Part 2, 2002, in wet and dry conditions. High quality resin enables smooth application and satin finish. Contains Ultra Violet light inhibitors, plus biocide which protects the oil against mould and algae growth.



Decking Stain & Seal

A tough water-resistant, matt finish. Contains Ultra Violet light inhibitors, plus biocide which protects the coating against mould and algae growth.



Timberlife

Protects and adds life to garden timber. The timber treatment that can be applied throughout the seasons.



Teak Oil

The original oil that enhances the natural beauty of all woods and veneers leaving an attractive low gloss finish.



4 Litre e