



SAFETY DATA SHEET
DECKING OIL CLEAR & COLOURS

Page: 1

Compilation date: 04/09/2012

Revision date: 03/01/2020

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DECKING OIL CLEAR & COLOURS

Product code: DOIL

Synonyms: DECKING OIL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd
Waterloo Road
Cricklewood
London
NW2 7TX
United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Skin Sens. 1: H317; Aquatic Chronic 3: H412; -: EUH208

Most important adverse effects: Contains cobalt octoate, methyl ethyl ketoxime. May produce an allergic reaction.
Flammable liquid and vapour. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains cobalt octoate, methyl ethyl ketoxime. May produce an allergic reaction.
H226: Flammable liquid and vapour.
H317: May cause an allergic skin reaction.
H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark

[cont...]

SAFETY DATA SHEET

DECKING OIL CLEAR & COLOURS

Page: 2



Signal words: Warning

Precautionary statements: P243: Take action to prevent static discharges.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water .
P321: Specific treatment (see instructions on this label)
P370+P378: In case of fire: Use media other than water to extinguish.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CALCIUM DRIER 4%

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	-	-	2.050%

WHITE SPIRIT

265-185-4	64742-82-1	-	-	0.196%
-----------	------------	---	---	--------

2-OCTYL-2H-ISOTHIAZOL-3-ONE

247-761-7	26530-20-1	-	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	0.064%
-----------	------------	---	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

[cont...]

SAFETY DATA SHEET
DECKING OIL CLEAR & COLOURS

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea. Nausea and stomach pain may occur.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Dry chemical powder. Carbon dioxide. Alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden. Avoid direct contact with the substance. Earth any equipment used in handling. Use non-sparking tools.

[cont...]

SAFETY DATA SHEET
DECKING OIL CLEAR & COLOURS

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. The floor of the storage room must be impermeable to prevent the escape of liquids. Keep container tightly closed. Keep away from sources of ignition. Keep away from direct sunlight.

Suitable packaging: Glass. Coated steel.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.05 mg/m ³	0.05 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure there is exhaust ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus must be available in case of emergency.

Hand protection: PVC gloves. Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing. PVC apron.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Clear and colour range

Odour: Paraffinic.

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Not miscible

Also soluble in: Most organic solvents.

Viscosity: Oily

Kinematic viscosity: 32

Viscosity test method: Flow time in seconds in a 3 mm ISO cup (ISO 2431)

[cont...]

SAFETY DATA SHEET
DECKING OIL CLEAR & COLOURS

Page: 5

Boiling point/range°C: No data available.	Melting point/range°C: No data available.
Flammability limits %: lower: No data available.	upper: No data available.
Flash point°C: 38	Part.coeff. n-octanol/water: No data available.
Autoflammability°C: No data available.	Vapour pressure: No data available.
Relative density: 0.86 @ 20C	pH: No data available.
VOC g/l: No data available.	

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-OCTYL-2H-ISOTHIAZOL-3-ONE

ORL	RAT	LD50	550	mg/kg
SKN	RBT	LD50	690	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact. There may be redness or whiteness of the skin in the area of exposure.

[cont...]

SAFETY DATA SHEET
DECKING OIL CLEAR & COLOURS

Page: 6

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea. Nausea and stomach pain may occur.

Inhalation: There may be shortness of breath with a burning sensation in the throat.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water. Absorbed only slowly into soil. Volatile.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

[cont...]

SAFETY DATA SHEET
DECKING OIL CLEAR & COLOURS

Page: 7

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: D/E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Other information: DANGER of spontaneous combustion. After use, any cloths or rags should ideally be immediately burnt but if this is not possible, then they should be washed in warm soapy water.

Even after washing the rags must never be crumpled into a ball but spread out and disposed of. Use synthetic fibre cloths where possible as natural fibres, especially cotton, increase the chances of spontaneous combustion.

Brushes and rollers should be cleaned with White Spirit and then washed in warm soapy water.

Phrases used in s.2 and s.3: EUH208: Contains cobalt octoate, methyl ethyl ketoxime. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H331: Toxic if inhaled.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.