

Quick  
Dry

**Rustins**

# Outdoor Clear Varnish

Longer lasting wood protection

Repels water  
and provides  
all year round  
outdoor  
wood protection.



**SATIN  
CLEAR**

Ideal for Outdoors

Doors/Frames

Window Frames

Cladding

Garden Furniture

Timber  
Conservatories

Summer Houses

Re-coatable  
in 4 hours

Resists blistering,  
cracking and peeling

Ultraviolet &  
fungicidal protection  
to protect the film

Non-yellowing

This is an attractive, quick drying, water-based, acrylic coating available in satin, matt and gloss finishes. It gives long lasting protection to external wood, allowing the natural grain to show through. It is milky white whilst liquid but dries to a clear colourless film.

### Preparation

The surface must be clean and free from dust, dirt and grease. Previously coated surfaces should be rubbed down to provide a key, but if the old finish is not in good condition, remove with Rustins Strypit Paint and Varnish Stripper. Do not use a blow lamp or caustic strippers. Wood should be smooth and sound prior to application.

### Application

**IMPORTANT: Stir well before use until there is no sediment on the bottom of the tin. If this is not done the varnish will dry with a gloss.**

Apply liberally across the grain with a full brush using the largest brush practical for the job. Synthetic soft tipped brushes designed for water based varnishes are recommended. Finish by brushing lightly with the grain taking care not to over brush. The first coat may be thinned with up to 15% water if applying in very warm conditions. Do not apply to warm surfaces or in strong direct sunlight if possible. If the first coat raises the grain, sand lightly with fine abrasive paper before applying another coat. 3 coats will provide adequate protection, but for improved durability, 4 coats are recommended. If the wood is porous or weathered, further applications may be required. The colour of bare wood may be changed with Rustins Wood Dyes. The varnish is ideal as a sealer for interior and exterior concrete. Do not use below 10°C, in damp conditions or if rain is imminent. **MAINTENANCE:** The finish will not flake or peel and will last many years if applied correctly. When re-coating is necessary, lightly sand the surface to key then clean with a mild detergent solution and water. Allow to dry then re-coat.

### Re-coating Time

The Varnish will be dry in approximately 30 minutes depending on the temperature and humidity, and further coats should be applied after a minimum of four hours. If applying over wood previously treated with a wood preservative test a small area first to ensure the varnish dries and adheres well. If the varnish fails to dry or adhere then the surface of the wood must be thoroughly cleaned with white spirit and steel wool or a plastic scouring pad.

### Coverage

1 litre will cover approximately 14 sq. metres one coat depending upon surface condition and porosity.

### Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

### HEALTH AND SAFETY

Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. May cause an allergic skin reaction. Causes serious eye irritation. Wash hands thoroughly after handling. If eye irritation persists: Get medical advice/attention. Contaminated work clothing should not be allowed out of the workplace. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



WARNING

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)


UFI: 9G97-FHFK-TP0A-9DU8

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom  
[rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Tel: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/e):  
130g/l (2010)  
This product contains max 55 g/l VOC



500ml e

Quick  
Dry

**Rustins**

# Outdoor Clear Varnish

Longer lasting wood protection

Repels water  
and provides  
all year round  
outdoor  
wood protection.



**GLOSS  
CLEAR**

**Ideal for Outdoors**

Doors/Frames

Window Frames

Cladding

Garden Furniture

Timber  
Conservatories

Summer Houses

Re-coatable  
in 4 hours

Resists blistering,  
cracking and peeling

Ultraviolet &  
fungicidal protection  
to protect the film

Non-yellowing

This is an attractive, quick drying, water-based, acrylic coating available in satin, matt and gloss finishes. It gives long lasting protection to external wood, allowing the natural grain to show through. It is milky white whilst liquid but dries to a clear colourless film.

### Preparation

The surface must be clean and free from dust, dirt and grease. Previously coated surfaces should be rubbed down to provide a key, but if the old finish is not in good condition, remove with Rustins Strypit Paint and Varnish Stripper. Do not use a blow lamp or caustic strippers. Wood should be smooth and sound prior to application.

### Application

Stir well before use. Apply liberally across the grain with a full brush using the largest brush practical for the job. Synthetic soft tipped brushes designed for water based varnishes are recommended. Finish by brushing lightly with the grain taking care not to over brush. The first coat may be thinned with up to 15% water if applying in very warm conditions. Do not apply to warm surfaces or in strong direct sunlight if possible. If the first coat raises the grain, sand lightly with fine abrasive paper before applying another coat. 3 coats will provide adequate protection, but for improved durability, 4 coats are recommended. If the wood is porous or weathered, further applications may be required. The colour of bare wood may be changed with Rustins Wood Dyes. The varnish is ideal as a sealer for interior and exterior concrete. Do not use below 10°C, in damp conditions or if rain is imminent. **MAINTENANCE:** The finish will not flake or peel and will last many years if applied correctly. When re-coating is necessary, lightly sand the surface to key then clean with a mild detergent solution and water. Allow to dry then re-coat.

### Re-coating Time

The Varnish will be dry in approximately 30 minutes depending on the temperature and humidity, and further coats should be applied after a minimum of four hours. If applying over wood previously treated with a wood preservative test a small area first to ensure the varnish dries and adheres well. If the varnish fails to dry or adhere then the surface of the wood must be thoroughly cleaned with white spirit and steel wool or a plastic scouring pad.

### Coverage

This tin will cover approximately 7 sq. metres one coat depending upon surface condition and porosity.

### Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### HEALTH AND SAFETY

Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o.

May produce an allergic reaction. May cause an allergic skin reaction. Causes serious eye irritation. Wash hands thoroughly after handling. If eye irritation persists: Get medical advice/attention. Contaminated work clothing should not be allowed out

of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)

UFI: 9697-FHFK-TP0A-9DU8

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)

Telephone: +44 (0)20 8450 4666



EU Limit value for this product (CAT A/e):  
130g/l (2010)  
This product contains max 55 g/l VOC



**500ml e**



WARNING



Quick  
Dry

# Rustins

## Outdoor Clear Varnish

Longer lasting wood protection

Repels water  
and provides  
all year round  
outdoor  
wood protection.



**MATT  
CLEAR**

Ideal for Outdoors

Doors/Frames

Window Frames

Cladding

Garden Furniture

Timber  
Conservatories

Summer Houses

Re-coatable  
in 4 hours

Resists blistering,  
cracking and peeling

Ultraviolet &  
fungicidal protection  
to protect the film

Non-yellowing

This is an attractive, quick drying, water-based, acrylic coating available in satin, matt and gloss finishes. It gives long lasting protection to external wood, allowing the natural grain to show through. It is milky white whilst liquid but dries to a clear colourless film.

### Preparation

The surface must be clean and free from dust, dirt and grease. Previously coated surfaces should be rubbed down to provide a key, but if the old finish is not in good condition, remove with Rustins Strypit Paint and Varnish Stripper. Do not use a blow lamp or caustic strippers. Wood should be smooth and sound prior to application.

### Application

**IMPORTANT: Stir well before use until there is no sediment on the bottom of the tin. If this is not done the varnish will dry with a gloss.**

Apply liberally across the grain with a full brush using the largest brush practical for the job. Synthetic soft tipped brushes designed for water based varnishes are recommended. Finish by brushing lightly with the grain taking care not to over brush. The first coat may be thinned with up to 15% water if applying in very warm conditions. Do not apply to warm surfaces or in strong direct sunlight if possible. If the first coat raises the grain, sand lightly with fine abrasive paper before applying another coat. 3 coats will provide adequate protection, but for improved durability, 4 coats are recommended. If the wood is porous or weathered, further applications may be required. The colour of bare wood may be changed with Rustins Wood Dyes. The varnish is ideal as a sealer for interior and exterior concrete. Do not use below 10°C, in damp conditions or if rain is imminent. **MAINTENANCE:** The finish will not flake or peel and will last many years if applied correctly. When re-coating is necessary, lightly sand the surface to key then clean with a mild detergent solution and water. Allow to dry then re-coat.

### Re-coating Time

The Varnish will be dry in approximately 30 minutes depending on the temperature and humidity, and further coats should be applied after a minimum of four hours. If applying over wood previously treated with a wood preservative test a small area first to ensure the varnish dries and adheres well. If the varnish fails to dry or adhere then the surface of the wood must be thoroughly cleaned with white spirit and steel wool or a plastic scouring pad.

### Coverage

1 litre will cover approximately 14 sq. metres one coat depending upon surface condition and porosity.

### Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

### HEALTH AND SAFETY

Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. May cause an allergic skin reaction. Causes serious eye irritation. Wash hands thoroughly after handling. If eye irritation persists: Get medical advice/attention. Contaminated work clothing should not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



WARNING

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)


UFI: 9G97-FHFK-TP0A-9DU8

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom  
[rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Tel: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/e):  
130g/l (2010)  
This product contains max 55 g/l VOC



**500ml e**