



Quick Dry

Rustins

Outdoor Wood Stain Stains & Finishes in One

SATIN
MEDIUM OAK



The above illustration shows 1 & 2 coats on bare wood.

- Longer-Lasting Outdoor Wood Protection
- Touch dry in 30 minutes
- Resists blistering, cracking & peeling
- Re-coatable in 4 hours
- Ultraviolet & fungicidal protection to protect the film
- Rinse brushes in water



STIR WELL BEFORE USE

Rustins Outdoor Wood Stain is a quick drying water-based acrylic decorative finish in attractive semi-transparent wood shades which will give long lasting protection to all external wood, allowing the natural grain to show through.

Preparation

The surface must be clean and free from dust, dirt and grease. Previously coated surfaces should be rubbed down to provide a key, but if the old finish is not in good condition, remove with Strypit Paint and Varnish Stripper. Do not use a blow lamp or caustic strippers. Wood should be smooth and sound prior to application.

Application

IMPORTANT: Stir well before use until there is no sediment on the bottom of the tin. If this is not done the varnish will dry with a gloss.

Stir well before use. Apply liberally across the grain with a full brush using the largest brush practical for the job. Synthetic soft tipped brushes designed for water based varnishes are recommended. Finish by brushing lightly with the grain taking care not to over brush. Try to keep a wet edge as overlapping a dry film will produce a darker patch as will drips and runs. The first coat may be thinned with up to 15% water if applying in very warm conditions. Do not apply to warm surfaces or in strong direct sunlight if possible. If the first coat raises the grain, sand lightly with fine abrasive paper before applying another coat. Bare wood requires 3 coats. If the desired colour is achieved with just 1 or 2 coats, use Rustins Outdoor Clear Varnish to a total of 3 coats. If the wood is porous or weathered extra coats may be required. The final colour will depend on the original colour of the wood and the number of coats applied. Do not use below 10°C, in damp conditions or if rain is imminent.

MAINTENANCE: The finish will not flake or peel and will last many years if applied correctly. When re-coating is necessary, lightly sand the surface to key then clean with a mild detergent solution and water. Allow to dry then re-coat.

Re-coating Time

The wood stain will be dry in approximately 30 minutes depending on the temperature and humidity, and further coats should be applied after a minimum of four hours. If applying over wood previously treated with a wood preservative test a small area first to ensure the wood stain dries and adheres well. If the coating fails to dry or adhere then the surface of the wood must be thoroughly cleaned with white spirit and steel wool.

Coverage

1 litre will cover approximately 14 sq. metres one coat depending upon surface condition and porosity.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o.

May produce an allergic reaction. Causes serious eye irritation. Wash hands thoroughly after handling. If eye irritation persists: Get advice/attention. Contaminated work clothing should not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

UFI: VX2E-YUT8-P103-Y4H6

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom
rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666


ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860

Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/e): 130g/l (2010)

This product contains max 55 g/l VOC



500mle



WARNING