

PRODUCT DATA SHEET

Product	Flexterior
Type	Flexible exterior oil based satin finish.
Intended Use	For the treatment of both soft and hardwood exterior joinery. It is ideally suited for doors, window frames, cladding, garden furniture and all smooth planed exterior timber. Available in Mahogany, Dark Oak, Teak and Clear.
Special Features	Highly water repellent, semi-transparent coloured finish which gives long term protection and colour enhancement without hiding the natural grain of the wood. Flexterior will not peel, crack or blister when correctly applied.
Preparation	Surfaces must be clean, dry and free of wax, grease and contaminants, smooth and sound. Fill large cracks, open joints and damaged areas with a high quality flexible filler. Clean oily woods, knots or resinous areas with white spirit and a rag. Remove mould, lichens, algae & moss with brush, scraper & domestic bleach, then rinse thoroughly and allow to dry.
Application	Apply by brush. The first coat may be thinned with one part White Spirit to nine parts
Coats	Three coats are recommended but porous end-grain or wood that is badly weathered may need further applications.
Drying Time	16-24 hours depending on temperature and humidity
Re-coating Time	16-24 hours depending on temperature and humidity
Application Temp.	Ideally 15-25°C. Do not use below 10°C or in conditions of high humidity
Coverage	15 sq. metres per litre per coat, depending on the absorbency of the wood.
Maintenance	When re-coating is necessary, clean down the surface with a mild detergent and water and allow to dry before coating.
Compatibility	May be applied over old existing coating if these are in good condition and rubbed down to provide a key. Coatings not in good condition should be removed with Rustins Strypit Paint and Varnish Stripper . If applying over wood preservatives test on a small area to ensure the varnish dries and adheres well. Cannot be applied over Creosote.
Settlement	STIR WELL BEFORE USE.
Shelf-life/Storage	Many years in normal conditions and if stored in original, tightly closed container.
Hazards	Flammable. Keep away from sources of ignition-No smoking. Avoid contact with skin and eyes. In case of contact with skin and eyes, rinse immediately with plenty of water and seek medical advice. Keep out of reach of children. A full Health & Safety Data Sheet is available upon request and on Rustins Web Site.
Clean-Up	Use White Spirit or Rustins Brush Cleaner whilst still wet. If dried on, clean equipment and brushes with Rustins Brush Restorer . Dried films can be removed with Rustins Strypit. Paint & Varnish Remover

Sizes

500ml

1 L

2.5 L