

SHAKE WELL BEFORE USE

Rustins Floor Oil is a unique blend of natural vegetable oils and resins which improve and enhances the beauty of all types of wooden floors. The Floor Oil is easy to apply using a brush, sponge or roller and dries to a natural finish. It is a penetrating oil drying to a hard durable and water resistant seal that brings out the beauty of the grain within the wood.

Preparation

The surface must be thoroughly clean, dry, dust-free, smooth, sound and free from timber treatments. Wax and contamination should be removed by scrubbing with **Rustins Surface Cleaner** or white spirit and plastic scouring pad, wiping away the solution formed, whilst still wet, with clean rags or kitchen paper towels. Existing coatings should be removed by sanding, after cleaning as above. Oily woods (e.g. Teak, Iroko) may be wiped with white spirit to improve the penetration of Floor Oil. Nailholes and narrow gaps may be filled with **Rustins Woodstopping**. **Change of colour:** Rustins Floor Oil will enhance the natural colour of the wood. Some wood may darken significantly when the oil is applied, particularly old or reclaimed wood. To ensure the result is as desired, coat a test area before proceeding. If a different shade is preferred, the bare wood can be stained with **Rustins Wood Dye** (11 natural wood shades). If other brands of dye or stain are to be used test before proceeding.

Application

Using a brush, sponge or roller apply liberally and allow to soak in. After about 5 minutes wipe off any excess oil on the surface using a sponge or rag. Ensure no pools remain to obtain an even finish.

Re-Coating Time

Apply a minimum of 3 coats initially. Allow 4-8 hours between coats depending on the temperature and humidity.

Maintenance

The floor should be vacuumed or swept then cleaned with a well wrung cloth or mop, using a mild detergent solution. Dirt and scratches are removed by rubbing with a plastic scouring pad. If the surface has become dull or worn it may be revived, after cleaning, by re-oiling.

Coverage

1 litre will cover approximately 13 sq.m per coat depending on the absorbency of the wood.

Cleaning

Clean brushes whilst wet with white spirit or **Rustins Brush Cleaner**. Remove as much product as possible from brushes before cleaning. Hard brushes can be cleaned with **Rustins Brush Restorer**.

Important

Rags used for oiling must be laid out flat to dry or destroyed otherwise they may catch fire due to spontaneous combustion.

Disposal (pollution prevention): some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.



EU Limit value for this product (CAT A/r):
700g/l (2010).
This product contains maximum 506g/l (VOC)

HEALTH AND SAFETY:

Flammable liquid and vapour. Use only outdoors or in a well-ventilated area. Wear eye protection.
IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTRE or doctor if you feel unwell.
In case of fire: Use carbon dioxide for extinction.
Contains gum turpentine, cobalt octoate, methyl ethyl ketoxime, naphtha. May produce an allergic reaction.



Warning

Please refer to Product Data Sheet for full information at www.rustins.co.uk


For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom or rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

Rustins

Floor Oil

Enhances the beauty of the grain

Natural finish • Easy to apply
Easy to maintain • Penetrating



1 Litre e
FLAMMABLE

For all types of
bare wood floors

1 Litre e
FLAMMABLE