

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Floor Oil</b>
<b>Type</b>	Rustin's Floor Oil is a mixture of natural vegetable oils and resins dissolved in white spirit, formulated to produce an attractive and durable finish.
<b>Intended Use</b>	For all interior wooden floors, including parquet, woodblock and floorboards.
<b>Special Features</b>	Brings out the natural beauty of the wood, the colour of the wood becomes richer. Easy to apply and maintain.
<b>Preparation</b>	The bare wood must be clean, smooth, dry and free from wax, dust and contaminants. Remove wax by scrubbing with White Spirit or <b>Rustin's Surface Cleaner</b> and a scouring pad, then wipe away whilst still wet with clean rags. Existing coatings should be removed by sanding, after cleaning as above. Oily woods (e.g. Teak, Iroko) may be wiped with White Spirit to improve the penetration of Floor Oil. Nail holes and narrow gaps may be filled with <b>Rustin's Wood Filler</b> . Do not apply <b>Rustins Knotting</b> .
<b>Application</b>	Ideally 15-25°C, do not apply below 5°C. Using a brush, sponge or roller apply liberally and evenly, allow to dry. If after about 10 minutes any pools of oil remain, remove by spreading evenly onto the surrounding areas using a sponge or rag, in order to obtain an even finish. Some wood may darken significantly when Floor Oil is applied, particularly old and reclaimed wood. To ensure the result is as desired, coat a test area before proceeding. If a different shade is preferred, the bare wood can be stained with <b>Rustin's Wood Dye</b> . If other brands of dye or stain are to be used, test before proceeding.
<b>Coats</b>	Apply a minimum of 3 coats initially.
<b>Drying Time</b>	4-8 hours depending on the temperature and humidity.
<b>Re-coating Time</b>	Allow 4-8 hours between coats depending on the temperature and humidity.
<b>Application Temp.</b>	Ideally 15-25°C, do not apply below 5°C.
<b>Coverage</b>	About 13 sq.m per Litre, 1 coat, depending on the absorbency of the wood.
<b>Maintenance</b>	The floor should be vacuumed or swept then cleaned with a well-wrung cloth or mop, using a mild detergent solution. Dirt and scratches are removed by rubbing with a plastic scouring pad. If the surface has become dull or worn it may be revived, after cleaning, by re-oiling.
<b>Compatibility</b>	Floor Oil may be used over the following Rustins products. Wood Dye, Grain Filler, and Wood Filler. Wood Dye can also be added to Floor Oil. Rustins Polyurethane Varnish can be applied over Rustins Floor Oil.
<b>Settlement</b>	Shake well before use.
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in normal cool, dry conditions.
<b>Hazards</b>	Flammable. Avoid contact with eyes and skin. Use in a well ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking. Keep container tightly closed. A full Safety Data Sheet is available upon request or on Rustins Web Site.

	<b>Important: Rags used for oiling should be laid out flat to dry, otherwise they may catch fire due to spontaneous combustion.</b>
<b>Clean-Up</b>	Clean brushes with White Spirit or <b>Rustin's Brush Cleaner</b> whilst still wet. Hard brushes can be cleaned with <b>Rustin,s Brush Restorer</b> . Hardened Oil can be reomoved using <b>Rustins Strypit</b>
<b>Sizes</b>	1Litre 5Litre