

Quick  
Dry

# Rustins

EST 1924

# SHED & FENCE CLEAR

Clear protection for sheds, fences  
and garden furniture



Up to 5 years protection

Harmless to pets and plants

Highly water repellent

UV Protection

Low Odour



**MATT FINISH**



Shed & Fence Clear is a high quality acrylic binder that includes waxes to give all external timber long lasting protection. It is resistant to ultra violet light and fading. Shed & Fence Clear is suitable for fences, sheds, trellis and all garden timber, new or previously treated.

## Preparation

Clean surface with a hard brush to remove algae, fungi, lichen and moss. Badly affected wood should be treated with Rustins Advanced Clear Wood Preserver and allowed to dry. Shed & Fence Clear may be applied over other fence and shed treatments and weathered creosote but paint or varnish should be removed with Strypit Paint & Varnish Stripper.

## Application

**STIR WELL BEFORE AND DURING USE.**  
Apply liberally using the largest brush suitable for the job. One coat is usually sufficient but on bare wood a minimum of two coats is required. Further applications can be made for added protection. Do not apply if rain is imminent or if temperature is below 10°C. Will not harm plants or clothes but splashes should be washed with water whilst still damp to prevent staining. Should not be applied in cold, damp conditions. Immediately after use clean brushes and hands with water.

## Re-coating Time

Approximately 30 minutes depending upon weather conditions and absorbency of the wood. Further applications can be made after 2 hours.

## Coverage

1 litre will cover approximately 6–12 sq. metres per litre for each coat, depending on condition of the wood.

## Cleaning

Remove as much product as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

## Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

## Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

## HEALTH AND SAFETY

Contains octhiliinone (ISO); 2-octyl-2H-isothiazol-3-one. May cause an allergic skin reaction.

Keep out of reach of children.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective clothing, eye protection, face protection.

IF ON SKIN: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/attention.

Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: MR96-VOCE-A008-KKSJ

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)



**WARNING**



EU Limit value for this product (CAT A1):  
130g/l (2010)  
This product contains max 56g/l VOC

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX  
United Kingdom  
[rustins@rustins.co.uk](mailto:rustins@rustins.co.uk)  
Tel: +44 (0)20 8450 4666

RO: Excellence Ltd,  
43 Grange Parade,  
Dublin D13 Y860 Ireland.  
Tel: +353 1 - 832 3300



**5Litre**