

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Small Job Gloss Paint</b>
<b>Type</b>	A high gloss, oil-based paint. The finish produced is tough, durable and resistant to oil and water.
<b>Intended Use</b>	A decorative coating for application over undercoat/ <b>Quick Drying Primer Undercoat</b> or over existing paints and varnishes on wood and metal. For interior and exterior use.
<b>Special Features</b>	A high gloss finish available in attractive 11 shades : Poppy (Red), Buttercup (Yellow), Magnolia, Candy Pink, County Cream, Delphinium(Pale Blue), Oxford Blue, Buckingham Green, Chocolate, Black and White. <b>Conforms to the Toy Safety Regulations BS EN 71 Part 3 1995.</b>
<b>Preparation</b>	The surface must be clean, smooth, sound, dry and free from wax, dust and contaminants. If the wood or metal surface is bare, apply the appropriate primer and undercoat before painting. On metal use <b>Rustin's Red Oxide Metal Primer</b> . On wood use <b>Rustin's Quick Drying Primer &amp; Undercoat</b> . Prior to painting, existing coated surfaces should be cleaned with <b>Rustin's Surface Cleaner</b> , or <b>Rustins Sugar Soap</b> and sanded lightly to provide a key, prior to painting. Cracks may be filled with <b>Rustin's Wood filler</b> . Undercoat may be applied if required.
<b>Application</b>	Apply light, even coats using a good quality brush. Heavy application can result in wrinkling.
<b>Coats</b>	1 coat is sufficient but a second coat may be applied if required. It is better to apply two light coats rather than one heavy coat. If too heavy a coat is applied the product will wrinkle. Sand lightly between coats if required.
<b>Drying Time</b>	Typically within 4-8 hours, depending on the temperature and humidity.
<b>Re-coating Time</b>	4-8 hours, depending on the temperature and humidity.
<b>Application Temp.</b>	Ideally, 15-25°C. Do not use below 10°C or in conditions of high humidity.
<b>Coverage</b>	12-15 sq.metres per litre depending on the absorbency of the surface.
<b>Maintenance</b>	The surface may be cleaned with a mild detergent solution or White Spirit as necessary. Worn areas may be re-coated once cleaned and lightly sanded to provide a key.
<b>Compatibility</b>	Compatible over most types of undercoat. Can be applied over top coats once thoroughly cleaned and lightly sanded to provide a key.
<b>Settlement</b>	<b>STIR WELL BEFORE USE</b>
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in cool dry conditions.
<b>Hazards</b>	Flammable. Keep out of reach of children. Use only in well ventilated areas. Keep away from sources of ignition – no smoking. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not white spirit. A full Health & Safety Data sheet is available upon request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	Clean brushes whilst wet with white spirit or <b>Rustins Brush Cleaner</b> . Remove excess product from brushes before cleaning. Hard brushes can be cleaned with <b>Rustins Brush Restorer</b> .
<b>Sizes</b>	250ml and 500ml, (certain colours).

