

Quick  
Dry

**Rustins**

# HEAT RESISTANT BLACK PAINT

**MATT FINISH**



Made in UK

**NOT FOR USE ON WOOD BURNING STOVES.**

#### STIR WELL BEFORE USE

Rustins Heat Resistant Paint is based on a high quality water-borne, cross-linking acrylic resin. It is for use on metal and wood and on both exterior and interior surfaces.

The maximum heat resistance is approximately 220°C.

#### Preparation

The surface must be clean and free from grease and wax. If already painted, remove flaking paint by scraping or use Rustins Strypit Paint and Varnish Stripper, remove all rust with a scraper or Rustins Rust Remover. Use Rustins Red Oxide Primer on bare metal; if applying to bare wood, apply a coat of Rustins Quick Drying Primer and Undercoat.

#### Application

Stir well before use until there is no sediment in the bottom of the can. Do not apply at temperatures below 10°C or in conditions of high humidity. Apply liberally with a synthetic fibre bristle brush. Two coats will provide adequate coverage, but three coats are recommended for improved durability. **MAINTENANCE:** The paint may be easily maintained by applying a further coat when required, cleaning the surface beforehand with a mild detergent solution.

#### Re-coating Time

The paint will be touch dry in approximately 30 minutes depending upon the temperature and humidity and can be re-coated after a minimum of two hours.

#### Coverage

This tin will cover approximately 7 sq m per coat.

#### Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water.

If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

#### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

#### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### HEALTH AND SAFETY

Contains a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o, surfactant #2, ammonia solution #2, butyl diglycol, 1,6 dihydroxy-2,5-dioxahexane. May produce an allergic reaction. Keep out of reach of children. Do not get in eyes, on skin, or on clothing. **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell. **IF ON SKIN:** Gently wash with plenty of soap and water. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wear protective gloves.

UFI: 5DNT-R3KU-FVOX-K0J4


Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)

For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROl: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT Aii): 130g/l (2010)  
This product contains max 110 g/l VOC



500ml e