

March 2018

PRODUCT DATA SHEET

Product	Jade Oil
Type	Oil-based product for use in specialised metal finishing processes.
Intended Use	Displacement of residual humidity/moisture from metal surfaces, protection of metal articles from handling and retardation of tarnishing.
Special Features	Displaces residual humidity/moisture from metal surfaces before to fix or after use of specialised metal-finishing processes, Also retards tarnishing by depositing a thin protective oil film. For interior use only.
Preparation	Dry the metal surface as much as possible with a soft cloth prior to application.
Application	Apply copiously to a clean cloth or using a brush, apply over metal surface or apply by spray over large areas.
Coats	One coat initially. Additional coats can be applied if required.
Drying Time	Allow to dry for 24 hours without handling.
Re-coating Time	Minimum 24 hours.
Application Temp.	Ideally 15-20° C.
Coverage	16 – 20 square metres per litre.
Maintenance	N/A
Compatibility	Compatible with most metals.
Settlement	N/A
Shelf-life/Storage	A considerable period of time if stored in a cool dry place with the container firmly sealed.
Hazards	Flammable. Harmful by inhalation, in contact with skin and if swallowed. Keep out of reach of children. Keep away from sources of ignition - no smoking. Use in well-ventilated area. Do not breathe vapour. Avoid contact with skin and eyes. A full Safety Data Sheet will be available upon request or on www.rustins.co.uk
Clean-Up	Remove from skin with soap and warm water. Clean application equipment with white spirit.
Sizes	To be agreed.