

June 2023

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Knotting &amp; White Knotting</b>
<b>Type</b>	Rustin's Knotting is based on pure shellac and alcohol; it is naturally brown in colour. White Knotting is also available which is made with bleached shellac.
<b>Intended Use</b>	For application to bare wood. Clean knots prior to priming/painting. To prevent discolouration of paint film.
<b>Special Features</b>	Fast drying. Prevents discolouration of paints. For interior and exterior use.
<b>Preparation</b>	The surface must be clean, bare and sanded smooth. Knotting prevents the discolouration of paint and is not designed to hold back excess resin in knots. Any excess resin should be removed using a heat gun prior to decorating. If there are cracks or holes around the knot, fill with <b>Rustins Woodfiller</b> , allow to dry, and sand smooth prior to applying Knotting.
<b>Application</b>	Using a brush apply Knotting liberally over the knot and surrounding area.
<b>Coats</b>	Apply 2 coats. Do not sand after application knotting.
<b>Drying Time</b>	Allow 1 hour between coats.
<b>Re-coating Time</b>	Allow 1 hr after final coat before applying primer.
<b>Application Temp.</b>	Ideally 15-25°C. Do not use below 10°C or in conditions of high humidity.
<b>Coverage</b>	10-12 sq. m per litre, 1 coat, depending on the absorbency of the surface.
<b>Maintenance</b>	N/A
<b>Compatibility</b>	Do not use under dyes, stains, water-based varnish and water based paints. If a water-based coating is to be used, first seal the knotting with an oil-based primer or undercoat, this will prevent the knotting discolouring the coating. Most types of oil-based wood primers may be applied over Knotting, including <b>Rustins Wood Primer</b> (Pink, White and Aluminium). If the knot needs filling, apply <b>Rustins Woodfiller</b> and sand smooth before applying Knotting.
<b>Settlement</b>	<b>SHAKE WELL BEFORE USE.</b>
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in normal conditions.
<b>Hazards</b>	Flammable. A full Safety Data Sheet is available on request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	Use Methylated Spirits to clean brushes and equipment. Use <b>Rustins Strypit</b> to remove dried films.
<b>Sizes</b>	125ml, 300ml, 500ml, (Knotting only), 1litre