



Quick
Dry

Rustins

Metal Paint


For indoor & outdoor
use on:

Bare Metal

Cast Iron

Galvanised Metal

Previous finishes



Smooth Satin Finish

Low VOC

Contains anti-corrosion
additives

No primer required

Low odour

Dry in 2 hours

STIR WELL BEFORE USE

Rustins Metal Paint is based on a water-borne, cross linking acrylic resin. It is for use on both bare and galvanised metal. It can be applied directly without the use of a primer and is suitable for indoor and outdoor use.

Preparation

The surface must be clean and free from grease and wax. If already painted, remove flaking paint by scraping or use Rustins Strypit Paint and Varnish Stripper. Remove loose rust with a wire brush. Where rust needs to be totally removed, use Rustins Rust Remover. Apply directly to bare metal but if applying to bare wood, apply a coat of Rustins Quick Drying Primer and Undercoat.

Application

Stir well before use until there is no sediment on the bottom of the can. Apply liberally with a synthetic fibre bristle brush. Two coats will provide adequate coverage, but three coats are recommended for improved durability. Do not apply at temperatures below 10°C or in conditions of high humidity. Do not apply on outdoor surface, when rain is imminent.

Re-coating Time

The paint will be touch dry in approximately 30 minutes depending on temperature and humidity and can be re-coated after a minimum of two hours.

Coverage

1 litre will cover approximately 14 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove as much paint as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Maintenance

The paint may be easily maintained by applying a further coat when required, cleaning the surface beforehand with a mild detergent solution.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains 5-chloro-2-methyl-2H-isothiazol-3-one. May produce an allergic reaction. Causes serious eye irritation. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

UFI: HP9W-FR70-3807-YC09


Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU limit value for this product (cat A/I):
130g/l (2010).
This product contains max 25g/l VOC



500ml e

