

February 2018

PRODUCT DATA SHEET

Product	Quick Dry Metal Paint
Type	Based on high quality water-borne cross linking acrylic resin.
Intended Use	A protective and decorative finish for bare metal, cast iron, aluminium and galvanised metal.
Special Features	No primer required, low odour, low VOC and quick drying. For interior and exterior use.
Preparation	The surface must be clean and free from grease and wax. If already painted, remove flaking paint by scraping or use Rustins Strypit, Paint and Varnish Stripper . Remove all rust with Rustins Rust remover . Can also be used on wood and concrete.
Application	Stir well before use until there is no sediment on the bottom of the tin. Apply liberally with a synthetic fibre bristle brush.
Coats	2 coats will provide adequate coverage but 3 coats are recommended for improved durability.
Drying Time	The paint will touch dry in approximately 30 mins depending upon temperature and humidity.
Re-coating Time	Re-coat after two hours.
Application Temp.	Ideally 15-25°C. Do not use below 10°C, or in conditions of high humidity.
Coverage	Coverage 14 sq metres/litre per coat.
Maintenance	Paint may be easily maintained by applying a further coat when required. Clean the surface with a mild detergent solution, lightly sand and re-apply.
Compatibility	If being applied to another finish carry out a small coating test to check for compatibility and adhesion.
Settlement	STIR WELL BEFORE USE.
Shelf-life/Storage	A very long time if stored in a cool dry place with the lid firmly secured. Do not store below 10 C and protect from frost.
Hazards	Harmful if swallowed. Keep out of reach of children. Rinse splashes from skin and eyes with clean water. A full Safety Data Sheet is available upon request or on www.rustins.co.uk
Clean-Up	Clean the brushes immediately with water. Hard brushes can be cleaned with Rustins Brush Restorer .
Sizes	250ml 500ml 1 L