

February 2017

PRODUCT DATA SHEET

| | |
|---------------------------|--|
| Product | Driveway and Patio Sealer |
| Type | A quick drying waterborne fluorine based polymer with transparent matt finish. |
| Intended Use | To seal old and new patio structures, pathways, and driveways. |
| Special Features | Resists water, alcohol, food oil, grease marks and motor oil. |
| Preparation | The surface must be clean and dry and free of any mould, fungal growth or solid matter likely to interfere with penetration of the sealer. Use Rustins Patio Cleaner to clean the surface. |
| Application | Shake container well and do not dilute the contents. Use a large paint brush or long haired roller and apply a liberal coat of Rustins Patio Sealer . Only apply one coat and allow the surface to dry for 24 hours. Depending on how the product is applied and the weather conditions, stone slabs will remain damp for up to one hour after product application. If correctly sealed, any water dropped on the surface after 24 hours will form beads. |
| Coats | Only apply one coat. |
| Drying Time | Surface will remain damp for up to one hour after product application. Allow to dry for 24 hrs after application. |
| Re-coating Time | N/A |
| Application Temp. | Min. application temp. 10 degrees C. Avoid use at high temperatures. |
| Coverage | 7-10 sq. metres per litre depending on absorbency of surface. |
| Maintenance | After 6 to 12 months carry out a beading test. If water no longer beads then clean and reapply the sealer. |
| Compatibility | Only apply to clean, bare and dry surfaces. |
| Settlement | Shake well before use. |
| Shelf-life/Storage | Many years if stored in original, tightly closed container in normal conditions. Protect from frost. |
| Hazards | Non-flammable. Flash point: Nil. General good practice advice: avoid contact with eyes, skin and clothing. A Full Safety Data Sheet is available upon request or on www.rustins.co.uk |
| Clean-Up | Water. |
| Sizes | 4 L. |