

March 2018

PRODUCT DATA SHEET

Product	Plastic Wood
Type	Quick drying wood filler.
Intended Use	For the repair of mouldings and broken edges, filling cracks and holes. Can be cut, filed, drilled and planed. When dry will take screws and nails.
Special Features	Can be used on wood, metal and stone. Available; Natural, Teak, Mahogany, White.
Preparation	The surface must be cleaned and dry and for best adhesion slightly roughened.
Application	Apply in thin layers with applicator or filling knife. When hard apply further layers, making sure that the final application has is higher than the surrounding area. When plastic wood has hardened, sand smooth.
Coats	As many layers as required.
Drying Time	4-6 hours, deep holes may take longer.
Re-coating Time	Do not re-apply until first application is dry.
Application Temp.	Ideally 15-25°C. Do not use below 5°C, or in conditions of high humidity.
Coverage	N/A
Maintenance	N/A
Compatibility	Can be painted varnished or stained. Please be aware that when stained, colour may vary from surrounding wood.
Settlement	Mix thoroughly if there are signs of separation.
Shelf-life/Storage	The shelf life of the product in an airtight container is indefinite. It is preferable to store the product in a cool place. It is important to replace the lid and ensure an airtight seal.
Hazards	Highly Flammable. Keep out of reach of children. Use only in well ventilated areas. Keep away from sources of ignition – no smoking. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent or White Spirit. Health and Safety Sheet available on Rustins Web Site.
Clean-Up	Clean tools with Cellulose Thinners.
Sizes	Tube 125ml tin