

SAFETY DATA SHEET

Woodfiller 638

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Woodfiller 638

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Wood filler

Relevant identified uses of the substance or mixture (REACH)

No special

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Rustins Ltd

Waterloo Road, London

NW2 7TX UK

Tel: +44(0)20 8450 4666

Fax: +44(0)208 452 2008

Contact person

Product Safety Department

E-mail

rustins@rustins.co.uk

SDS date

2020-11-11 SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

Safety statement(s)

General

P101, If medical advice is needed, have product container or label at hand.
 P102, Keep out of reach of children.

Prevention

P210, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271, Use only outdoors or in a well-ventilated area.

Response

-

Storage

P403+P233, Store in a well-ventilated place. Keep container tightly closed.

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

Hazardous substances

ethyl acetate

2.3. Other hazards

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/Ingredient name	Identifiers	% w/w	Classification	Note
ethyl acetate	CAS No.: 141-78-6 EC No.: 205-500-4 REACH No.: 01-2119475103-46-XXXX Index No.: 607-022-00-5	40-60%	STOT SE 3, H336 Eye Irrit. 2, H319 Flam. Liq. 2, H225 EUH066	EU
Cellulose, nitrate	CAS No.: 9004-70-0 EC No.: 618-392-2 REACH No.: Index No.:	10-15%	Flam. Sol. 1, H228	
Propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: Index No.: 603-117-00-0	3-5%	STOT SE 3, H336 Eye Irrit. 2, H319 Flam. Liq. 2, H225	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes,	CAS No.: 64742-48-9	1-3%	Flam. Liq. 3, H226 Asp. Tox. 1, H304	

cyclics, <2% aromatics	EC No.: 919-857-5	STOT SE 3, H336 EUH066
	REACH No.: 01- 2119463258-33	
	Index No.:	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

EU: European occupational exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbon dioxide, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste.

See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.

Avoid static electricity.

Smoking, drinking and consumption of food is not allowed in the work area.

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Storage temperature

Temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

— ethyl acetate
 Long term exposure limit (8 hours) (ppm): 200
 Short term exposure limit (15 minutes) (ppm): 400

— Cellulose
 Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)
 Short term exposure limit (15 minutes) (mg/m³): 20 (inhalable)

— Propan-2-ol
 Long term exposure limit (8 hours) (ppm): 400
 Long term exposure limit (8 hours) (mg/m³): 999
 Short term exposure limit (15 minutes) (ppm): 500
 Short term exposure limit (15 minutes) (mg/m³): 1250

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
 EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

Product/Ingredient name	DNEL	Route of exposure	Duration
Propan-2-ol	26 mg/kg bw/day	Oral	Long term – Systemic effects - General population
Propan-2-ol	319 mg/kg bw/day	Dermal	Long term – Systemic effects - General population
Propan-2-ol	888 mg/kg bw/day	Dermal	Long term – Systemic effects - Workers
Propan-2-ol	89 mg/m ³	Inhalation	Long term – Systemic effects - General population

PNEC

Product/Ingredient name	PNEC	Route of exposure	Duration of Exposure
Propan-2-ol	28 mg/kg	Soil	No data available
Propan-2-ol	2251 mg/l	Sewage Treatment Plant	No data available
Propan-2-ol	140,9 mg/l	Marine water	No data available
Propan-2-ol	552 mg/kg	Marine water sediment	No data available
Propan-2-ol	140,9 mg/l	Freshwater	No data available
Propan-2-ol	552 mg/kg	Freshwater sediment	No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, eating and drinking are not allowed in the work premises

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements


Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.


Respiratory Equipment

Work situation	Type	Class	Colour	Standards
-	AX	-	Brown	EN14387




Skin protection

Work situation	Recommended	Type/Category	Standards
	Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-



Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
	Butyl	0.7	> 480	EN374-2, EN374-3, EN388, EN421



Eye protection

No specific requirements

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Paste

Colour

Various colours

Odour

Testing not relevant or not possible due to nature of the product.

Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

1.10

Viscosity

Testing not relevant or not possible due to nature of the product.

Phase changes

Melting point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

76.00 °C

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Evaporation rate (n-butylacetate = 100)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

-4.00 °C

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Explosion limits (% v/v)

Testing not relevant or not possible due to nature of the product.

Explosive properties

Testing not relevant or not possible due to nature of the product.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Product/Ingredient name	Species	Test	Route of exposure	Result
ethyl acetate	Rat	LD50	Oral	5600 mg/kg ·
ethyl acetate	Rat	LC50	Inhalation	56000 mg/l/4h ·

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

Propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/Ingredient name	Species	Test	Duration	Result
ethyl acetate	Fish	LC50	96 hours	>200 mg/l ·
ethyl acetate	Daphnia	EC50	48 hours	>700 mg/l ·
ethyl acetate	Algae	IC50	72 hours	>100 mg/l ·

12.2. Persistence and degradability

Product/Ingredient name	Biodegradability	Test	Result
ethyl acetate	Yes		

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

EWC code

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

ADR/RID

UN- or ID number	UN proper shipping name	Transport hazard class	PG	Tunnel restriction code
1133	ADHESIVES	3	II	2 (D/E)

IMDG

UN- or ID number	UN proper shipping name	Transport hazard class	PG	EmS
1133	ADHESIVES	3	II	F-E, S-D

IATA

UN- or ID number	UN proper shipping name	Transport hazard class	PG
1133	ADHESIVES	3	II

"MARINE POLLUTANT"

No

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

P5c

Additional information

Tactile warning.

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

The Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H336, May cause drowsiness or dizziness.

H319, Causes serious eye irritation.

H225, Highly flammable liquid and vapour.

EUH066, Repeated exposure may cause skin dryness or cracking.

H228, Flammable solid.

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the substance/mixture is based on:

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.