

Rustins

Sanding Sealer

Ideal for turned wood & marquetry



Shellac based
sealer used to
seal wood before
waxing for a
professional
finish



Rustins

Shellac Sanding Sealer

This product contains pure shellac and alcohol with a special additive included to facilitate sanding when dry.

It should be used to seal the surface prior to French polishing and waxing, but is often used as a finish in its own right, as it dries to a hard, clear film. Sanding Sealer should also be used to seal penetrating Wood Dyes to prevent them bleeding when varnishes containing white spirit are applied.

DIRECTIONS

Shake well before use. Apply in a warm, dry atmosphere. The wood should be clean and smooth and stained, if necessary, before application with Rustins Wood Dyes. Apply liberally with a soft brush or pad and allow to dry. The drying time will be between 1-1/2 hours, depending upon temperature and humidity. Rub down lightly with fine glasspaper before applying a second coat. When used as a finish, rub with 00 or 000 steel wool and wax polish, finishing with a soft cloth or yellow duster.

Clean brushes with Methylated Spirits.

Warning



Highly flammable liquid and vapour.
Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

In case of fire: Use carbon dioxide for extinction.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point.

UFI: AV5P-PM7Q-V91N-GKJV

Please refer to Product Data Sheet for full information at www.rustins.co.uk



5 015332 1470037 > **500ml e**



For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666

RO1: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland.
Tel: +353 1 - 832 3300