

### PRODUCT DATA SHEET

<b>Product</b>	<b>Strypit – New Formula</b>
<b>Type</b>	Non Caustic. Dichloromethane free paint and varnish stripper.
<b>Intended Use</b>	For removing paint, varnish, cellulose, polyurethane, emulsion, French Polish, lacquer and textured finishes from wood, metal, glass or plaster.
<b>Special Features</b>	Specially formulated to avoid stripping the attractive patina acquired through age on old furniture. Free from acid and caustic.
<b>Preparation</b>	Ensure suitable safety protection is worn prior to commencing job.
<b>Application</b>	Brush on a thin coat of <b>Strypit</b> to provide a “key”. Dab on a second application liberally after 10 minutes. Test with a knife before scraping to ensure the paint is completely penetrated. Do not allow the surface to dry up. Apply a second liberal coat and ensure that this is worked into the blistered, softened paint. Leave for further 35 to 40 minutes. The paint/varnish should now be free from the surface and easy to remove. If not apply more <b>Strypit</b> . On curved surfaces or mouldings use a wire brush or steel wool.
<b>Coats</b>	Apply 2 or more liberal applications depending on finish and substrate. On old paint or very heavy applications <b>Strypit</b> can be left on longer to maximise application.
<b>Drying Time</b>	Do not allow surface to dry during stripping. Apply more product if necessary.
<b>Re-coating Time</b>	Apply second application after 10 minutes. Repeat after 35-40 minutes if paint not fully stripped.
<b>Application Temp.</b>	Ideally 15-25°C.
<b>Coverage</b>	1 litre will remove approximately 5 square meters.
<b>Maintenance</b>	N/A
<b>Compatibility</b>	Should not be used on certain plastics or fibre glass.
<b>Settlement</b>	Shake well before use.
<b>Shelf-life/Storage</b>	The shelf life of the product in an airtight container is a very long period of time. Store the product in a cool dry place.
<b>Hazards</b>	Highly Flammable. Keep away from all source of ignition – NO SMOKING. Keep out of reach of children. Do not breathe vapour. Take precautionary measures against static discharge. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear suitable protective clothing and gloves. A full Safety Data Sheet is available upon request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	After stripping, wooden surfaces should be rubbed with the grain with grade 2 or grade 3 steel wool and white spirit and then wiped with a clean rag. On all other surfaces wipe with a clean rag and water. Water can be used on wooden surfaces, but would cause the grain to swell. Clean brushes using White Spirit or water.
<b>Sizes</b>	250ml 500ml 1 L 2.5 L 5 L

