



Quick Dry

Rustins

EST 1924

TimberLife

up to **5** year protection for all your outdoor timber...



**LOW ODOUR -
HIGHLY WATER
REPELLENT**

**ALLOWS THE TIMBER
TO 'BREATHE'**

RESISTANT TO FADING

**PROTECTS TIMBER
THROUGH ALL EXTREMES
OF WEATHER**

**HARMLESS TO
PETS & PLANTS**

TimberLife is made in a range of attractive colours and contains a high quality acrylic binder, preservatives and waxes to give all external timber long lasting protection from rot and mould.

The special pigments are resistant to ultra violet light and fading. TimberLife is suitable for fences, sheds, trellis and all garden timber, new or previously treated.

Preparation

Clean surface with a wire brush to remove algae, fungi, lichen and moss. Badly affected wood should be treated with a fungicide and allowed to dry. TimberLife may be applied over other fence and shed treatments and weathered creosote but paint or varnish should be removed with Strypit Paint & Varnish Stripper.

Application

STIR WELL BEFORE AND DURING USE.

Apply liberally using the largest brush practicable for the job. One coat is usually sufficient but on bare wood a minimum of two coats is required.

Further applications can be made for a deeper colour. Do not apply if rain is imminent or if temperature is below 5°C. Will not harm plants or clothes but splashes should be washed with water whilst still damp to prevent staining. Immediately after use clean brushes and hands

with water. If brushes dry out and become hard, clean with cellulose thinners.

Re-coating Time

Approximately 30 minutes depending upon weather conditions and absorbency of the wood. Further applications can be made after 2 hours.

Coverage

1 litre will cover approximately 6-12 sq. metres per litre for each coat, depending on condition of the wood.

Cleaning

Remove as much product as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

HEALTH AND SAFETY

Contains ochilinone (ISO); 2-octyl-2H-isothiazol-3-one. May cause an allergic skin reaction.

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective clothing, eye protection, face protection.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

UFI: 9RYS-HSCR-H70K-EV7C

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Tel: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/e): 130g/l (2010)
This product contains max 55 g/l VOC



1 litre e



WARNING