

# Rustins

## QUICK DRY Varnish TOUCH DRY IN 30 MINUTES

### SATIN OAK

Long lasting  
wood protection

For all types of  
interior wood

Clean brushes  
in water



#### STIR WELL BEFORE USE

Rustins Quick-Drying Coloured Varnish is a low odour durable acrylic finish that is touch-dry in 20 minutes. It will give long-lasting protection to all interior wood.

#### Preparation

The surface must be clean and free from wax, grease and dirt. Previously varnished surfaces should be rubbed down to provide a key, but if the old finish is not in good condition, remove it with Rustins Paint and Varnish Stripper. New wood should be sound and sanded smooth prior to application. Knotting should not be applied over knots.

#### Application

Stir well before use. Apply liberally across the grain using a synthetic fibre brush specially made for water-based finishes. Finish off by brushing lightly with the grain, taking care not to over-brush. Try to keep a wet edge as overlapping a dry film will produce a darker patch, as will drips and runs. The first coat may be thinned with up to 10% water if applying in very warm conditions. If the first coat raises the grain, sand lightly with fine abrasive paper before applying a further coat. The varnish will be touch-dry in approximately 20 minutes, depending on the temperature and humidity. Further coats should be applied after a minimum of 2 hours. Three coats are recommended, but as each extra coat will make the colour deeper, if the colour is satisfactory after 1 or 2 coats, apply one or more coats of Rustins Quick-Drying Clear Acrylic Varnish. The final colour will depend on the original colour of the wood and the number of coats applied. Do not apply at temperatures below 10°C or in conditions of high humidity.

#### Re-coating Time

The varnish will be touch dry in approximately 20 minutes depending upon the temperature and humidity and can be re-coated after a minimum of two hours.

#### Coverage

This tin will cover approximately 7 sq metres one coat depending on the absorbency of the wood to which the varnish is applied.

#### Cleaning

Remove as much varnish as possible and return to this container. Brushes should then be cleaned immediately with water. If the brushes become hard, they may be cleaned with Rustins Brush Restorer or Rustins Cellulose Thinners.

#### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

#### Storage

Store in a cool dry place with the lid tightly closed. Protect from frost.

#### Important

The colour illustrated on the tin is an indication only of the colour and the varnish should always be tested on a small area first to make sure the colour is correct. Do not transfer the varnish into an unlacquered metal container. Use glass or polythene containers. If water splashes onto the surface within 3 days of application, it should be wiped of with a soft cloth.

#### HEALTH AND SAFETY

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Wear protective gloves. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

UFI: 616V-YRR8-5A1X-HSF3

Please refer to Product Data Sheet for full information at [www.rustins.co.uk](http://www.rustins.co.uk)


For information on Rustins' products visit our website at [www.rustins.co.uk](http://www.rustins.co.uk) or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom [rustins@rustins.co.uk](mailto:rustins@rustins.co.uk) Telephone: +44 (0)20 8450 4666

ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300



EU Limit value for this product (CAT A/E): 130g/l (2010)

This product contains max 126g/l VOC



500ml e