



SAFETY DATA SHEET

WOOD DYE

Page: 1

Compilation date: 08/11/2017

Revision date: 03/01/2020

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WOOD DYE

Synonyms: WOOD DYE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road

Cricklewood

London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315

Most important adverse effects: Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 2

Signal words: Warning

Precautionary statements: P280: Wear eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call POISON CENTER/doctor if you feel unwell.

P370+P378: In case of fire: Use media other than water to extinguish.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

3-BUTOXYPROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-878-4	5131-66-8	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	20.950%

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	0.751%
-----------	---------	---	---	--------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	0.501%
-----------	------------	---	---	--------

MESITYLENE

203-604-4	108-67-8	-	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	0.125%
-----------	----------	---	--	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea. There may be shortness of breath due to congestion of the lungs.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol resistant foam. Do not use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Flammable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Transfer to a suitable container.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Earth any equipment used in handling. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep away from direct sunlight. Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 4

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

1,2,4-TRIMETHYLBENZENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	125 mg/m ³	-	-	-

MESITYLENE

UK	25 ppm	-	-	-
----	--------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colour Range

Odour: Paraffinic.

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Not miscible

Also soluble in: Benzene.

Viscosity: Non-viscous

Boiling point/range°C: 150-190

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 38

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.850 @ 20 C

pH: No data available.

VOC g/l: No data available.

[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Sources of ignition. Direct sunlight. Heat.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

3-BUTOXYPROPAN-2-OL

SKN	RBT	LD50	3100	mg/kg
-----	-----	------	------	-------

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

MESITYLENE

IPR	GPG	LDLO	1303	mg/kg
-----	-----	------	------	-------

[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 6

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be vomiting and diarrhoea. There may be shortness of breath due to congestion of the lungs.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: D/E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any

[cont...]

SAFETY DATA SHEET

WOOD DYE

Page: 8

damage resulting from handling or from contact with the above product. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.