

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Quick Dry Worktop Oil</b>
<b>Type</b>	Quick dry Worktop Oil is a unique water-borne blend of natural plant oils and other special ingredients to nourish and protect all types of timber. The plant oils originate from sustainable sources and are used largely to replace crude oil derived components used in synthetic resins.
<b>Intended Use</b>	For all kind of interior hardwood and kitchen worktops.
<b>Special Features</b>	It is a penetrating oil drying to a hard durable and water resistant seal. It adds warmth and depth to all woods, including oak, beech, teak, mahogany and veneered surfaces. It does not leave a surface film to scratch or chip. Conforms to Plastic materials and Articles in contact with Food (England) Regulations 2008.
<b>Preparation</b>	The surface must be clean, smooth, dry and free from wax, dust and contaminants. Remove wax by scrubbing with White Spirit or Rustin's Surface Cleaner and a scouring pad, then wipe away whilst still wet with clean rags. Existing oil should be removed with Rustin's Strypit Paint and Varnish Stripper. Bare wood may be dyed before coating with Rustin's Wood Dye.
<b>Application</b>	Apply liberally with a clean rag or brush and wipe off the surplus oil after a few minutes. The first coat should be applied liberally with a brush and allowed to dry without wiping. Nibs may be removed from the final coat by applying the oil with a scouring pad, rubbing in the direction of the grain, then wiping away the surplus with clean rags or paper kitchen towels. Some wood may need sanding between two coats.
<b>Coats</b>	Bare wood requires 3 coats.
<b>Drying Time</b>	2-3 hours depending on temperature and humidity.
<b>Re-coating Time</b>	Re-coat once the previous coat is dry.
<b>Application Temp.</b>	Ideally 15-25°C, do not apply below 10°C.
<b>Coverage</b>	Approx. 13sq.m per litre, 1 coat, depending on the absorbency of the wood.
<b>Maintenance</b>	Clean with white spirit, sand lightly and apply further coats when needed to be re-coated.
<b>Compatibility</b>	Worktop Oil may be used over the following Rustin's products. Wood Dye, Grainfiller, and Woodfiller.
<b>Settlement</b>	Shake well before use.
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in cool, dry conditions.
<b>Hazards</b>	Keep out of reach of children. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear suitable protective clothing and gloves. Health & Safety Data Sheet is available on request or on Rustins Web Site.

<b>Clean-Up</b>	Clean brushes with warm water and detergent. If dried on, clean brushes with Rustins Brush Restorer.
<b>Sizes</b>	Sizes 500ml 1litre