

Rustins Primer

For use on bare wood

White

For indoor & outdoor use



STIR WELL BEFORE USE

Rustins White Primer is a high quality oil based primer, suitable for all interior and exterior wood.

Preparation

The wood must be clean bare and sanded smooth. Seal knots with Rustins Knotting before priming. Holes and cracks should be filled with Rustins Wood Filler after priming.

Application

Stir well before use. Using a brush, apply evenly. One coat is usually sufficient, two coats may be required. Sand lightly between coats if necessary.

Re-coating Time

Touch dry in 2-4 hours. Allow to dry for 12 hours before applying undercoat.

Coverage

This tin will cover approximately 3.75 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove excess product from brushes before cleaning whilst wet with white spirit or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed.

HEALTH AND SAFETY

Flammable liquid and vapour.

Contains cobalt octoate, methyl ethyl ketoxime.

May produce an allergic reaction.

May cause drowsiness or dizziness.

Use only outdoors or in a well-ventilated area.

Wear eye protection.

IF ON SKIN (or hair):

Remove immediately all contaminated clothing. Rinse skin with water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.

In case of fire: Use carbon dioxide for extinction.

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom

rustins@rustins.co.uk

Telephone: +44 (0)20 8450 4666




WARNING



EU Limit value for this product (CAT A/g):
350g/l (2010)

This product contains max 304 g/l VOC



250ml e