

## SHAKE WELL BEFORE USE

Briwax Liquid Beeswax is specially formulated to nourish and protect sealed or unsealed wood. Quick drying and ideal for use on absorbent woods such as pine and oak. Ideal for use on interior wooden furniture such as wood panelling, tables, wood balustrades and beams.

### Preparation

The timber surface should be first sealed with an oil, varnish or sanding sealer ideally from the Rustins/Briwax Range and ensure that the surface is clean prior to application of the wax. Previously applied wax should be clean thoroughly with Rustins Surface Cleaner. This product is not suitable for use on bare wood but may be applied over wood that has been treated with Briwax Sanding Sealer, Rustins Danish Oil, Rustins Teak Oil, Rustins French Polish or one of the range of Rustins Varnishes.

### Application

Apply with a clean soft cloth or duster, rubbing evenly over the surface. Leave for 60 minutes then polish off, with moderate pressure, using a soft clean cloth or duster.

### Re-Coating Time

The surface should be dry within 1-1½ hours and can be re-coated after 1½ hours. Apply 2 or more coats allowing sufficient drying time in between coats. Do not use below 10°C.

### Maintenance

Regular maintenance is recommended to keep surfaces in good condition. Clean surface with a cloth or duster and re-apply as required. Do not wash with water. If compatibility with previously coated surface is not known, then carry out a small coating test in an inconspicuous area.

### Coverage

1 litre covers approximately 12 square metres per coat depending on the absorbency of the wood.

### Cleaning

Wash hands in soapy water.

### Important

Rags used for waxing must be laid out flat to

dry or destroyed, otherwise they may catch fire due to spontaneous combustion.

### Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes/coatings. Do not empty product into drains or watercourses.

### Storage

Store in a cool dry place with lid tightly closed. Protect from frost.

### Warning

**H226:** Flammable liquid and vapour.

**H317:** May cause an allergic skin reaction.

**H412:** Harmful to aquatic life with long lasting effects.

**P243:** Take precautionary measures against static discharge.

**P303+361+353:** IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

**P273:** Avoid release to the environment.

**P280:** Wear protective gloves.

**P321:** Specific treatment (see instructions on this label).

**P370+378:** In case of fire: Use carbon dioxide for extinction.

**P210:** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

**P233:** Keep container tightly closed.

**P261:** Avoid breathing fumes.

**P302+352:** IF ON SKIN: Wash with plenty of soap and water.

**P333+313:** If skin irritation or rash occurs: Get medical advice/attention.

For information on Briwax products visit our website at [www.briwax.co.uk](http://www.briwax.co.uk) or contact us at Briwax International, Waterloo Road, London, NW2 7TX United Kingdom [sales@briwax.co.uk](mailto:sales@briwax.co.uk)  
Telephone: +44 (0)20 8450 4666

**BRIWAX**



1 Litre e



**BRIWAX**

**BRIWAX**

**LIQUID  
BEESWAX**

with pure turpentine

*Nourishes & protects interior wood  
Safe for toys*

1 Litre e

Manufactured in England by Briwax International