

BRIWAX Recognised as the best furniture wax throughout the world

Rustins/Briwax Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.briwax.co.uk

June 2014

PRODUCT DATA SHEET

Product	BRIWAX LIQUID BEESWAX - Clear
Туре	Clear beeswax solution
Intended Use	Used to nourish and protect sealed wood
Special Features	Ideal on new and old furniture and all types of timber previously sealed. Prevents timber from drying out.
Preparation	The timber surface should be first sealed with an oil, varnish or sanding sealer ideally from the Rustins/Briwax Range and ensure that the surface is clean prior to application of the wax. Previously applied wax should be removed with Rustins or Briwax Wax Polish Remover .
Application	Apply with a clean soft cloth or duster, rubbing evenly over the surface. Leave for a 60 minutes then polish off, with moderate pressure, using a soft clean cloth or duster.
Coats	Apply 1 or more coats allowing 1 hour between coats.
Drying Time	30 – 60 minutes.
Re-coating Time	60 minutes.
Application Temp.	15-20 C
Coverage	10-12 square litres per meter
Maintenance	Clean surface with cloth or duster and re-apply as required. Do not wash with water.
Compatibility	This product is not suitable for use on bare wood but may be applied over wood that has been treated with Rustins/Briwax Sanding Sealer, Danish Oil, Teak Oil, French Polish or one of the range of Rustins Varnishes
Settlement	SHAKE WELL BEFORE USE
Shelf-life/Storage	The shelf life of the product in an airtight container is a very long period of time. Store in a cool dry place
Hazards	Flammable. Avoid contact with eyes and skin. Use in a well ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking. Keep container tightly closed. A full safety data sheet is available upon request or on www.briwax.co.uk
Clean-Up	Wash hands after use in warm soapy water
Sizes	500mls 1Litre