



Manufactured in England
by Briwax International

FINISHING WITH LIMING WAX

A smooth paste which will produce a white grain finish on most woods. Can be applied to bare or stained wood.

Coverage: 4 - 5 square metres per 220gm

Quick Drying: 30 minutes per coat

Surface Preparation: Prepare by sanding along the grain with a fine sand paper. Some wood would benefit by opening the grain with a wire brush.

Application: Apply sparingly with a cloth rubbing well into the grain, removing the excess, so that a uniform colour is obtained. Allow to dry then buff with a soft cloth. For a higher sheen overcoat Liming Wax with Clear Briwax.

For information on Briwax products visit our website at www.briwax.co.uk or contact us at Briwax International, Waterloo Road, London, NW2 7TX UK
sales@briwax.co.uk Telephone: +44 (0)20 8450 4666



WARNING

Flammable liquid and vapour.

Contains Naphtha.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Use only outdoors or in a well-ventilated area.

In case of fire: Use carbon dioxide for extinction.

Wear protective gloves.

Read label before use.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing fumes.

Avoid release to the environment.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Collect spillage.



BRIWAX

A smooth paste
Liming Wax

For a white grain

220g e