



Manufactured in England  
by Briwax International

## FINISHING WITH LIMING WAX

A smooth paste which will produce a white grain finish on most woods. Can be applied to bare or stained wood.

- Coverage:** 4 - 5 square metres per 220gm  
**Quick Drying:** 30 minutes per coat  
**Surface Preparation:** Prepare by sanding along the grain with a fine sand paper. Some wood would benefit by opening the grain with a wire brush.  
**Application:** Apply sparingly with a cloth rubbing well into the grain, removing the excess, so that a uniform colour is obtained. Allow to dry then buff with a soft cloth. For a higher sheen overcoat Liming Wax with Clear Briwax.

For information on Briwax products visit our website at [www.briwax.co.uk](http://www.briwax.co.uk) or contact us at Briwax International, Waterloo Road, London, NW2 7TX UK  
[sales@briwax.co.uk](mailto:sales@briwax.co.uk) Telephone: +44 (0)20 8450 4666



### WARNING

Flammable liquid and vapour.

Contains Naphtha.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Use only outdoors or in a well-ventilated area.

In case of fire: Use carbon dioxide for extinction.

Wear protective gloves.

Read label before use.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing fumes.

Avoid release to the environment.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Collect spillage.

**BRIWAX**

A smooth paste  
**Liming Wax**

*For a white grain*



220g e