



Recognised as the best furniture wax throughout the world

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

February 2018

PRODUCT DATA SHEET

Product	Briwax Liming Wax
Type	Smooth White Tinted Wax Paste
Intended Use	To produce a white grained finish in opened grained timbers
Special Features	Can be applied directly onto bare wood. A more even appearance will however be obtained if the timber is sealed first.
Preparation	Ensure the surface is clean, dry and free from any previous finishes. Some woods will benefit from opening the grain first with a wire brush. Stain or seal the timber prior to applying the wax.
Application	Work the Briwax Liming Wax into the wood and wipe over with a clean cloth to remove the excess. Liming Wax can be over coated with Clear Briwax to give a more durable finish.
Coats	One application is usually sufficient but a second coat can be applied after 15 minutes
Drying Time	Drying time in good conditions is 15 minutes.
Re-coating Time	15 minutes. Liming Wax can be over coated with Clear Briwax to give a more durable finish.
Application Temp.	Ideally 15 -20 C
Coverage	N/A
Maintenance	Wipe over with clean dry cloth when necessary. Reapply Clear Briwax if necessary.
Compatibility	Compatible with all types of timbers. For best results and to prevent a blotchy appearance timber should always be previously sealed with a varnish, oil or Briwax Shellac Sanding Sealer .
Settlement	N/A
Shelf-life/Storage	A very long time if stored in original container tightly sealed in a cool dry place.
Hazards	Flammable. Keep out of reach of children. Keep container tightly closed. Keep away from all sources of ignition-No smoking. A full Health & Safety Data Sheet is available upon request or on www.briwax.co.uk
Clean-Up	Hands and application cloth can be cleaned in warm soapy water.
Sizes	220 gms