

## BRIWAX Recognised as the best furniture wax throughout the world

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

## February 2018

## PRODUCT DATA SHEET

Product	Shellac Sanding Sealer
Туре	A traditional sealer formulated from natural harvested shellac derived from sustainable resources
Intended Use	Suitable for sealing all types of wood prior to waxing or French polishing.
Special Features	Contains additives which facilitate sanding once dry. Used in combination with <b>Briwax</b> or <b>Briwax Original</b> , a complete grain enhancing finish may be applied to uncoated shelves, architraves, banisters, skirting, softwood dado rails or timber furniture in an afternoon.
Preparation	Wood should be clean, dry and smooth. Sand in direction of grain to produce a smooth surface. If grain is open, fill with <b>Rustins Grain Filler</b> . Furniture that is to be renovated should be cleaned with white spirit and fine wire wool to ensure that it is free from grease and wax. Wood staining should be carried out before applying <b>Briwax Shellac Sanding Sealer</b> .
Application	Apply liberally with a soft brush or cloth pad and allow to dry. Rub down lightly with flour paper or Briwax 0000 Wire Wool before applying a second coat. When used as a finish, polish with a soft cloth or yellow duster.
Coats	As a finish, apply as many coats as required to build a sufficient layer of shellac. For sealing wood prior to waxing, apply 2 liberal coats.
Drying Time	20 – 30 minutes
Re-coating Time	30 minutes
Application Temp.	Ideally 15 - 25°C
Coverage	8 – 10 square metres per litre
Maintenance	Wipe with damp cloth. Greasy or dirty surfaces should be cleaned with a mild non-abrasive liquid detergent. Avoid using harsh cleaning agents. Wax polishes may be used.
Compatibility	Wood may be dyed with <b>Rustins Wood Dyes</b> and/or filled with <b>Rustins Grain Filler</b> prior to sealing with <b>Briwax Shellac Sanding Sealer</b>
Settlement	Shake well before use.
Shelf-life/Storage	A very long time if stored in original sealed container in a cool dry place.
Hazards	Highly flammable. Irritating to eyes. Vapours may cause drowsiness. Keep away from children. Keep away from all sources of ignition. No smoking. A full Health & Safety Data Sheet is available on request or from www.antiquax.co.uk
Clean-Up	All equipment must be cleaned whilst wet with methylated spirit.
Sizes	500 ml tins