

FINISHING WITH BRIWAX PREMIUM TEAK OIL

Feeds and seals bare timber, enhances the beauty of wood and produces a satin finish. Shake well before use.

Apply liberally with a clean cloth or brush.

Remove surplus oils after a few minutes.

On new wood two or three coats will be necessary to produce the required finish.

PRODUCT PROPERTIES

Coverage: 5-10 square metres per 1 litre.

Quick Drying: Touch dry in 4-8 hours depending on conditions.

Cleaning: Clean brushes with white spirit.

Surface Preparation: Lightly sand with a good quality glass paper. Remove all dust to provide dry clean surface free from grease and wax.

Application: Apply liberally with a clean cloth or brush.

Allow to soak in and even up with a dry cloth. Allow to dry.

Apply further coats following the same procedure.

For information on Briwax products visit our website at www.briwax.co.uk or contact us at Briwax International, Waterloo Road, London, NW2 7TX United Kingdom
sales@briwax.co.uk Telephone: +44 (0)20 8450 4666

Repeated exposure may cause skin dryness or cracking.

Contains cobalt octoate, methyl ethyl ketoxime.

May produce an allergic reaction.

Flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

BRIWAX TEAK OIL

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye protection.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.



WARNING



1 Litre e



PREMIUM TEAK OIL

*For all varieties of wood
& veneered surfaces*

1 Litre e

Manufactured in England by Briwax International