

FINISHING WITH BRIWAX PREMIUM DANISH OIL

Feeds and seals bare timber, enhances the beauty of wood and produces a matt finish. Shake well before use.
Apply liberally with a clean cloth or brush.
Remove surplus oils after a few minutes.
On new timber two or three coats may be necessary to achieve the required finish.

PRODUCT PROPERTIES

Coverage: 5-10 square metres per litre
Quick Drying: Touch dry 4-8 hours depending on temperature and conditions.
Cleaning: White spirit
Surface Preparation: Ensure timber is dry and free from contaminants such as grease and wax. Lightly sand with a good quality glass paper. Remove all dust.

For information on Briwax products visit our website at www.briwax.co.uk or contact us at Briwax International, Waterloo Road, London, NW2 7TX United Kingdom
sales@briwax.co.uk Telephone: +44 (0)20 8450 4666

HEALTH & SAFETY

Repeated exposure may cause skin dryness or cracking.

Contains cobalt 6, methyl ethyl ketoxime. May produce an allergic reaction.

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.

In case of fire: Use carbon dioxide for extinction.



WARNING

BRIWAX



1 Litre e



Made in UK

BRIWAX

PREMIUM
DANISH
OIL

*Low Sheen Covering which
Seals and Finishes Bare Wood*

1 Litre e

Manufactured in England by Briwax International