



Recognised as the best furniture wax throughout the world

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

February 2018

PRODUCT DATA SHEET

Product	Danish Oil
Type	A blend of oils, resins and driers formulated to seal and feed all varieties of wood. Briwax Danish Oil produces an attractive and durable low gloss finish. For a satin finish use Rustins Danish Oil . For a high sheen effect use Briwax Teak Oil .
Intended Use	For all interior and exterior bare wood, i.e. doors, joinery garden and indoor furniture.
Special Features	Brings out the natural beauty of wood and veneered surfaces, giving an open-grained low lustre finish. Easy to maintain, drying without leaving a surface film to damage.
Preparation	The wood must be clean, smooth, dry and free from wax, dirt or other surface contaminants. Oily hardwoods such as Iroko or Teak must be washed down by scrubbing with white spirit or Rustins Surface Cleaner and a scouring pad, then wipe away whilst still wet with clean rags. Existing paint or varnish should be removed with Rustins Strypit Paint and Varnish Stripper . Bare wood may be dyed prior to coating with Rustins Wood Dye . It is recommended that oak is first treated with Rustins Clear Advanced Wood Preserver to prevent dark staining caused by mould naturally found in oak. Do not apply knotting.
Application	Apply liberally with a clean rag or brush, allow to soak in and wipe off the surplus oil after a few minutes. On exterior wood, the first coat should be applied liberally and allowed to dry without wiping. Nibs may be removed from the final coat with a scouring pad, rubbing in the direction of the grain, then wiping away the surplus oil with clean rags.
Coats	Bare wood requires 2 - 3 coats. Exterior woodwork will require additional coats
Drying Time	4 – 8 hours depending on temperature and humidity
Re-coating Time	4 – 8 hours depending on temperature and humidity
Application Temp.	Ideally 15 – 25°C. Do not apply below 10°C and when rain is expected while working outdoors.
Coverage	5 – 10 square metres per litre depending on absorbency of the wood.
Maintenance	Periodic re-oiling is required. For use outdoors, re-oiling should be carried out at least annually. Before re-oiling clean surfaces thoroughly with white spirit.
Compatibility	Briwax Danish Oil may be used over Rustins Wood Dye, Grainfiller or Woofiller . The dye may also be added to Briwax Danish Oil , (max. 30%), which may also be used as a wood primer before applying undercoat. Rustins Polyurethane Varnish may be applied over Briwax Danish Oil at any time. The surface must be clean before varnishing.
Settlement	Shake tin well before use.
Shelf-life/Storage	Many years if stored in original sealed container in cool dry conditions.
Hazards	Flammable. Avoid contact with skin and eyes. Use in a well-ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking. Keep container tightly closed. A full safety data sheet is available on request or on www.briwax.co.uk Important: rags used for oiling must be laid out flat to dry, otherwise they may catch fire due to spontaneous combustion.
Clean-Up	Clean brushes with white spirit or Rustins Brush Cleaner whilst still wet. If oil is dried on, clean brushes with Rustins Brush Restorer .
Sizes	5 litres tins.