



Recognised as the best furniture wax throughout the world

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

February 2018

PRODUCT DATA SHEET

Product	Satin Hard Wax Oil
Type	Briwax Satin Hard Wax Oil is a mixture of natural vegetable oils, waxes and resins dissolved in white spirit giving an attractive, durable finish.
Intended Use	For internal woodwork subject to a high degree of wear; i.e. wood flooring.
Special Features	Brings out the natural beauty of the wood. Makes wood colours become richer. Easy to apply and maintain; leaving a wear, water and stain resistant finish to woodwork.
Preparation	The wood must be bare, or sanded clean of any previous coatings. The wood must also be smooth, dry and free from wax, dust and surface contaminants. Remove any waxes present with Rustins Surface Cleaner and a scouring pad. Wipe off residues with clean rags. Oily timbers such as Teak or Iroko must be wiped over with white spirit to remove surface oils which may inhibit drying and penetration of Briwax Satin Hard Wax Oil . Nail holes or narrow gaps may be filled with Rustins Wood Filler . Do not use knotting.
Application	Use a brush, sponge or roller. Apply evenly in the direction of grain. Leave for a few minutes, then remove excess pools of material using a sponge or rag, spreading surplus oil evenly over the surrounding area. Note; Briwax Satin Hard Wax Oil may darken some woods, therefore coating a test area first is advised. Rustins Wood Dye may be used under or in Briwax Satin Hard Wax Oil if desired. Test before proceeding if other brands of wood colourant are to be used.
Coats	Apply a minimum of 2 coats initially.
Drying Time	4 -6 hours, depending on temperature and humidity.
Re-coating Time	4 -6 hours, depending on temperature and humidity.
Application Temp.	Ideally 15-25 deg. C. Do not apply below 5 deg. C.
Coverage	20 – 30 sq. m. per litre, depending on the nature of the wood.
Maintenance	The floor should be vacuumed or swept, then cleaned with a well-wrung cloth or mop, using a mild detergent solution. Dirt and scratches may be removed by rubbing with a plastic scouring pad. If the surface has become dull or worn, it may be revived by re-oiling after cleaning.
Compatibility	Briwax Satin Hard Wax Oil may be used over the following Rustins products: Rustins Wood Dye, Grain/Wood/Gap Filler. Rustins Wood Dye may be added to Briwax Satin Hard Wax Oil . Rustins Polyurethane Varnish may be applied over Briwax Satin Hard Wax Oil .
Settlement	Stir well before use.
Shelf-life/Storage	Many years in original sealed packaging if stored in cool, dry conditions.
Hazards	Flammable. Avoid contact with eyes and skin. Use in a well-ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking while using. Keep container tightly closed. Full Product and Safety Data Sheets are available on request or from www.briwax.co.uk
Clean-Up	Clean brushes with white spirit or Rustins Brush Cleaner if still wet. Hard brushes may be cleaned with Rustins Brush Restorer . Hardened oil may be removed using Rustins Strypit Paint & Varnish remover .
Sizes	1L, 2.5L.