

 DANGER 		UN No. 1263
Flammable Solid	Toxic to aquatic life with long lasting effects	
H228 - Flammable solid. H411 - Toxic to aquatic life with long lasting effects. P210 - Keep away from sparks - No smoking. P273 - Avoid release to the environment	P280 - Wear protective gloves. P370/P378 - In case of fire: Use carbon dioxide for extinction. P391 - Collect spillage. UFI: 0WQ3-50F7-G001-E3UJ	
Briwax International. Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666		

DIRECTIONS FOR USE	
	BRIWAX is a fast drying blend containing natural waxes suitable for use on most wooden surfaces.
	SURFACE PREPARATION: Unsealed wooden surfaces should be smooth, dry and clean. Apply BRIWAX using a lint free cloth or 0000 steel wool thoroughly working the wax into the grain. Once dry buff to desired finish with a clean soft cloth. Improved shine and durability can be achieved by first sealing the surface with BRIWAX Sanding Sealer. For antiques and pre-finished furniture, first check compatibility, then apply BRIWAX in small areas with a clean soft cloth. The BRIWAX finish can be maintained by further applications which will give increased hardness and shine.
	This product is not recommended for use in areas where it will come in contact with water. Above 20°C BRIWAX will soften and liquify. Replace lid, put in a cool place and it will return to its original state.
For information on Briwax products visit our website at www.briwax.co.uk or contact us at Briwax International, Waterloo Road, London, NW2 7TX United Kingdom sales@briwax.co.uk Telephone: +44 (0)20 8450 4666 ROI: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. Tel: +353 1 - 832 3300	

Content 370gms e


the natural wax



CLEANS, STAINS AND POLISHES