

## BRIWAX Recognised as the best furniture wax throughout the world

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

## June 2019

## PRODUCT DATA SHEET

|                    | i kebesi balah silai  |
|--------------------|---|
| Product            | Briwax (Toluene-free)   |
| Туре               | A high quality wax polish based on natural waxes to provide a simple, easy finishing system for unfinished/raw timber or over French polished surfaces in the home or in a workshop.  |
| Intended Use       | Suitable for use on most raw or sealed wooden surfaces.   |
| Special Features   | Easy to apply and buff. Gives a long lasting satin sheen. Rapid drying. Can be applied directly to timber or onto Briwax Shellac Sanding Sealer. Available in Clear and 13 shades; Medium Brown (P7), Rustic Pine, Antique Mahogany, Honey, Antique Brown, Old Pine, Dark Oak, Jacobean (181), Teak Walnut. Toluene-free, low odour version of <b>Briwax Original</b> .                       |
| Preparation        | The surface must be smooth, clean and dry. <b>Briwax</b> may be used on previously waxed surfaces. For best results, clean surface first with <b>Briwax Furniture Cleaner</b>   |
| Application        | Apply using a lint free cloth or <b>Briwax 0000 Steel Wool</b> , thoroughly working the wax into the grain. When dry buff to desired finish with a soft clean cloth. Note; best results are obtained if the wood has previously been coated with <b>Briwax Shellac Sanding Sealer</b> .   |
| Coats              | One coat is usually sufficient, but a second coat may be applied to obtain a higher sheen.  |
| Drying Time        | Quick drying.   |
| Re-coating Time    | If required, re-apply after a few minutes.  |
| Application Temp.  | Ideally 15-25°C.  |
| Coverage           | N/A   |
| Maintenance        | Re-apply as required.   |
| Compatibility      | Compatible with French Polish-type wood finishes. If in doubt or when waxing antiques or prefinished furniture, check compatibility first. For best results and to prevent a blotchy appearance on porous woods, seal untreated surface with <b>Briwax Danish Oil or Shellac Sanding Sealer.</b> Note; this product is unsuitable for use where it will come into contact with water or heat. |
| Settlement         | N/A   |
| Shelf-life/Storage | A very long time, if stored in the original sealed container in a cool dry place.   |
| Hazards            | Flammable. Keep out of reach of children. Keep Container tightly closed. Keep away from all sources of ignition. No smoking. Avoid inhalation of fumes or eye/skin contact. Full Health & Safety Data is available on request or from <a href="https://www.briwax.co.uk">www.briwax.co.uk</a>   |
| Clean-Up           | Hands and application cloth may be cleaned in warm soapy water.   |
| Sizes              | 370 g tins, 5 kg tins (limited colours)   |
|                    |   |