



www.antiquax.co.uk

Waterloo Road, London NW2 7TX
Telephone: +44(0)20 8450 4666

TECHNICAL DATA SHEET

Antiquax Original Wax Polish

SH, AXLH250 and EL500

Type	A very high quality traditional type polish based upon premium performance waxes, carnauba and beeswax, reinforced with a blend of hydrocarbon waxes to aid application and improve durability.
Intended Use	For regular use on all fine natural wood and antique furniture.
Special Features	Easy application. Provides a long lasting durable wax finish with soft mellow sheen to enhance grain and patina. Silicone free. Resists dust and fingerprinting.
Preparation	The surface must be clean and dry. Antiquax Original Wax Polish can be used on previously waxed surfaces. For best results initially clean the surface with Antiquax Furniture Cleaner .
Application	Apply sparingly, using a soft lint free cloth, in a circular motion. Work well into the grain and allow to dry to a light haze. Remove by polishing in a circular motion using a clean dry cloth.
Coats	One coat is usually sufficient but a second coat may be applied to obtain a higher sheen.
Drying Time	Quick drying.
Re-coating Time	Re-apply if required after a few minutes.
Application Temp.	Ideally 15-25°C
Coverage	N/A
Maintenance	Re-apply when necessary.
Compatibility	Compatible with most timber finishes. If in doubt check on an inconspicuous test area. For best results and to prevent a blotchy appearance, timber should be previously sealed with a varnish, oil or sanding sealer.
Settlement	N/A
Shelf-life/Storage	A very long time if stored in original sealed container in a cool dry place.
Hazards	Flammable. Keep away from children. Keep container tightly closed. Keep away from all sources of ignition. No smoking. A full Health & Safety Data Sheet is available on request or on www.antiquax.co.uk
Clean-Up	Hands and application cloths can be cleaned in warm soapy water.
Sizes	100, 250 and 500 ml tins

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.