



WARNING

EUH208: Contains gum turpentine. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+340: IF INHALED: Remove victim to fresh air

and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P370+378: In case of fire: Use carbon dioxide for extinction.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261: Avoid breathing fumes.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

Antiquax

45 Waterloo Road, London NW2 7TX

Telephone: +44 (0)20 8450 4666

www.antiquax.co.uk



Antiquax

NATURAL BEESWAX

Polishes and cleans all wooden surfaces


Antiquax Natural Beeswax is based on pure natural beeswax for use on previously sealed surfaces.

Application: Using a clean cotton cloth or brush, apply the Beeswax in the direction of the wood grain where possible. To obtain a consistent finish, always wipe evenly, blending the Beeswax over the whole surface area by exerting a small degree of pressure when applying by hand. Take care to lightly remove any excess Beeswax immediately with a separate, clean absorbent cloth, again following the direction of the grain pattern. Leave to dry for around 10 minutes, and buff to finish with a soft cloth. The application of additional coats will

deepen the existing shade and enhance the sheen level.

Preparation: For use on previously finished or sealed wood. Ensure all surfaces are free from dust or blemishes before application. For bare wood, use Rustins Sanding Sealer or Rustins Danish Oil to seal the wood before applying Antiquax Natural Beeswax. Previously waxed surface must be cleaned with Rustins Surface Cleaner or white spirit before applying the wax.

Coverage: 16 sqm per Litre (depending on substrate and method of application)



5 015332 000593 >

250ml e