TECHNICAL DATA SHEET



Antiquax Natural Beeswax

Waterloo Road, London NW2 7TX Telephone: +44(0)20 8450 4666

ANTIQLX

Туре	A traditional clear formulation using only refined Natural Beeswax, linseed oils and genuine turpentine.
Intended Use	Used to clean and revive the natural colour of wood and enrich the patina of all good furniture. Can be used for restoration of antique furniture.
Special Features	Easy to apply with soft cloth. Produces deep rich sheen. Leaves a pure clean aroma.
Preparation	The surface must be clean and dry. Antiquax Natural Beeswax can be used on previously waxed surfaces. For best results initially clean the surface with Antiquax Furniture Cleaner.
Application	Apply to the surface with a soft lint free cloth, lightly in small areas working with the grain Antiquax Natural Beeswax dries quickly. Once dry, buff with lint free cotton cloth to achieve a desired sheen.
Coats	One coat is usually sufficient but a second coat may be applied to obtain a higher sheen.
Drying Time	Quick drying.
Re-coating Time	Re-apply if required after a few minutes.
Application Temp.	Ideally 15-25° C
Coverage	N/A
Maintenance	Re-apply when necessary.
Compatibility	Compatible with all types of timber finishes. For best results and to prevent a blotchy appearance timber should always be previously sealed with a varnish, oil or sanding sealer.
Settlement	N/A
Shelf-life/Storage	A very long time if stored in original container tightly sealed in a cool dry place.
Hazards	Flammable. Keep out of reach of children. Keep container tightly closed. Keep away from all sources of ignition-No smoking. A full Health & Safety Data Sheet is available upon request or on www.antiquax.co.uk
Clean-Up	Hands and application cloth can be cleaned in warm soapy water.
Sizes	250 mls