TECHNICAL DATA SHEET



Antiquax Chopping Board Oil

Waterloo Road, London NW2 7TX Telephone: +44(0)20 8450 4666

ANTIQOIL

Туре	Antiquax Chopping board Oil is a unique water-borne blend of natural plant oils and other special ingredients to nourish and protect all types of solid wood chopping boards and worktops.
Intended Use	For protecting all type of solid timber chopping boards and worktops.
Special Features	The oil contains anti-microbial additives with a slow release formula which provides protection against a wide range of bacteria including E-Coli and MRSA. Antiquax Chopping Board Oil conforms to the Articles In Contact With Food Regulations.
Preparation	The wood must be clean, smooth, dry and bare. Existing paint and varnishes should be removed with Rustins Strypit Paint and Varnish Remover.
Application	Apply liberally with a clean rag or brush and wipe off the surplus oil after a few minutes. The first coat should be applied liberally with a brush and allowed to dry without wiping. Nibs may be removed from the final coat by applying the oil with a scouring pad, rubbing in the direction of the grain, then wiping away the surplus with clean rags or paper kitchen towels.
Coats	Bare wood requires 3 coats.
Drying Time	2-3 hours depending on temperature and humidity.
Re-coating Time	Re-coat once the previous coat is dry.
Application Temp.	Ideally 15-25°C, do not apply below 10°C.
Coverage	Approx. 13sq.m per litre, 1 coat, depending on the absorbency of the wood.
Maintenance	Periodic re-oiling required. Clean surfaces before re-oiling using mild detergent and warm water.
Compatibility	Compatible with all types of timbers.
Settlement	Shake well before use.
Shelf-life/Storage	Many years if stored in original, tightly closed container in cool place.
Hazards	Keep out of reach of children. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear suitable protective clothing and gloves. Important: Rags used for oiling should be laid out flat to dry; otherwise they may catch fire due to spontaneous combustion.
Clean-Up	Remove as much oil as possible from brushes before cleaning. Clean brushes whilst wet with water and mild detergent.
Sizes	250 ml