



March 2018

PRODUCT DATA SHEET

Product	Floorboard Gap & Joint Filler
Type	A flexible, highly bodied acrylic emulsion for filling properties
Intended Use	For filling gaps or joints in woodwork up to 2 mm in combination with a mixture of saw/sanding dust to optimise colour match with original timber. Note; unsuitable for gaps wider than 2 mm. Do not use on gaps within planks or on end-grain floors.
Special Features	Non-yellowing, low odour, quick drying, water-washable
Preparation	The surface must be clean, sanded smooth and free of wax, dust and contaminants
Application	Mix Wudcare Floorboard Gap & Joint Filler to a thick cream-like consistency with saw or sanding dust saved from carpentry work. Apply using a stainless steel trowel across whole floor. Once hard-dried, sand floor smooth.
Coats	One or two coats as required
Drying Time	Minimum 20 minutes before sanding, depending on filler depth and consistency
Re-coating Time	Minimum 20 minutes before re-coating, depending on filler depth and consistency
Application Temp.	Min. 10 deg. C
Coverage	8 – 12 sq. /metres per litre, depending on porosity and quantity of filling required
Maintenance	Not applicable
Compatibility	Check compatibility, but should be suitable for use under most emulsion or oil-based paints
Settlement	Stir well before use
Shelf-life/Storage	Many years if suitably stored unopened in original container above 5 deg. C. Protect from fro
Hazards	Non-flammable. Avoid contact with eyes and skin. In case of contact with eyes, immediately rinse with plenty of water and seek medical attention. After contact with skin, wash immediately with soap and water or a suitable skin cleanser. Keep out of reach of children.
Clean-Up	Clean equipment with water immediately after finishing work. If product is allowed to dry on, clean equipment with Rustins Brush Restorer .
Sizes	1 L.