

### UN number 1133

### WUDCARE

# INSTANT BOND CONTACT ADHESIVE

Instantly bonds to: Woods, Plastics, Cork, Rubber, Leather, Fabrics and Plaster



## **500ml** $\Theta$

A general purpose contact adhesive that forms a strong permanent bond to a wide variety of materials such as: Decorative Laminates (e.g. Formica), Chipboard, Plywood, Blockboard, Hardboard, Plasterboard, Natural Wood Veneers, Cement, Asbestos, Rubber, Neoprene Rubber, Canvas and Leather.

#### PREPARATION:

- Stir adhesive before use and make sure that surfaces to be bonded are clean, dry and free from dust and grease.
- Condition materials to be bonded (particularly wood composites and decorative laminates) in the bonding environment overnight.

#### APPLICATION:

- 1. Apply a thin even coat of adhesive to both surfaces using a short, stiff brush.
- 2. When surfaces become 'touch dry' (i.e. adhesive is glossy and no longer transfers to the knuckles) align the bond edges and bond under maximum pressure. For best results, laminates should be nip rolled or platen pressed. If this is not possible use a hard roller and go over the entire working surface using as much bodyweight as possible. Seams and edges should always receive extra pressure. If possible sandwich the panel edge between wooden battens and use G-clamps.
- The newly bonded material should not be subjected to extreme pressure changes for 3-4 days after bonding and avoid further fabrication until the adhesive has fully cured.

ALWAYS RE-SEAL AFTER USE.

Store the adhesive in a dry area away from heat or cold.

### Health & Safety

H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains ROSIN. May produce an allergic reaction.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces,

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapour/spray.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection.

Contains:Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, less than 5% n- hexane, Ethyl Acetate and Rosin.

Wudcare Products, 51 Waterloo Road, London NW2 7TX UK. Tel:+44(0)20 8450 4666 Fax: +44 (0)20 8452 2008 Email: info@wudcare.co.uk www.wudcare.co.uk

DANGER

\*