



September 2015

PRODUCT DATA SHEET

Product	Liquifix
Type	A versatile, non-hazardous zero VOC penetrating lubricant and rust preventative suitable for use around the office, home and garden.
Intended Use	Use as a lubricant for any sliding or moving part. Frees up fixed components. Also prevents rust and corrosion.
Special Features	Non-toxic, non-corrosive, zero VOC, non-staining, odourless. Spray applied material that is safe to use around the home. Non-conductive. Penetrating – can free up fixed components. Water repellent, prevents rust and corrosion.
Preparation	The bare wood must be clean, smooth, dry, and free of dust and contaminants.
Application	Spray onto any sliding or moving part as required.
Coats	Not applicable.
Drying Time	Not applicable
Re-coating Time	Not applicable
Application Temp.	Ideally 15-25°C but do not apply below 5°C.
Coverage	Not applicable
Maintenance	Not applicable
Compatibility	Not applicable
Settlement	SHAKE WELL BEFORE USE.
Shelf-life/Storage	Many years if stored in original, tightly closed container in cool, dry conditions.
Hazards	Avoid contact with eyes and skin. Use in a well-ventilated area. Keep out of reach of children. Avoid direct contact with flames. A full Safety Data Sheet is available upon request.
Clean-Up	Clean with soap and water.
Sizes	60ml, 120ml and 250ml