

# Charter Aluminium Wood Primer

1 Litre e

**Charter Aluminium Wood Primer** has many advantages over normal primers and is superior to other products of a similar character. May be used on all types of wood and under most types of paint except cellulose. Particularly suitable for Oregon Pine and the more resinous types of timber and if applied over old creosoted wood should prevent bleeding. When used correctly on properly treated timber should seal knots, stop porosity and resist damp. Apply by brush to clean, dry and suitably prepared surface and DO NOT rub down between coats. Normally recoatable after 18-24 hours but when sealing creosote etc allow 48 hours between coats.

#### Health & Safety

**Flammable liquid and vapour • May be fatal if swallowed and enter airways • May cause drowsiness or dizziness • Toxic to aquatic life with long lasting effects • Harmful in contact with skin • May cause an allergic skin reaction • Causes serious eye damage • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources • Keep out of reach of children • Keep container tightly closed • If medical advice is needed have product container or label at hand • Do not get in eyes, on skin or on clothing • Keep cool • Wear protective gloves/protective clothing/eye protection/face protection.**

**IF ON SKIN (or hair) Take off immediately all contaminated clothing. Rinse skin with water/shower.**

**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**



#### WARNING

Contains: White Spirit index 64742-88-7

VOC Content High 25-50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution  
EU limit value for this product (Cat A/1): 600g/l (2007) / 500g/l (2010). This product contains max 440g/l VOC

**Brummer, Waterloo Road, London NW2 7TX Tel: +44 (0)20 8450 4666**

**Email: [sales@woodfillers.co.uk](mailto:sales@woodfillers.co.uk)**