

Product	Charter Aluminium Wood Primer
Type	A spirit-based self-knotting aluminium wood primer in an oil-based medium.
Intended Use	Suitable for use on new and old wood and other surfaces and under most types of paint, excluding cellulosic coatings.
Special Features	Ideal for use on resinous timber including pine. May be applied over previously creosoted work to prevent bleeding. May be used as a primer on asbestos sheeting. Stops porosity, resists damp, Acts as a barrier against sap and moisture, minimising the risk of blistering. Sufficiently elastic to prevent cracking or flaking. Dries to a hard metallic surface.
Preparation	Ensure that area to be primed is clean, dry and free from any particles of dirt or grease.
Application	Apply with a clean brush and ensure the area to be covered is completely coated.
Coats	1 - 2 coats.
Drying Time	Min. 6 hours or preferably overnight. DO NOT rub down or sand the metallic structure which acts as a barrier to stop resin and damp coming through the coating. Damage to the dried film will affect the sealing properties of the coating. When completely dried undercoat may be applied.
Re-coating Time	Normally recoatable after 18 – 24 hours. When sealing creosote or treated timbers allow 48 hours between coats to allow the protective surface to seal. DO NOT rub down or sand the metallic structure which acts as a barrier to stop resin and damp coming through the coating. Damage to the dried film will affect the sealing properties of the coating. When completely dried undercoat may be applied.
Application Temp.	Ideally 15-25 deg. C. Do not apply below 10 deg. C.
Coverage	Approximately 15 sq. metres per litre per coat depending on substrate and coating thickness
Maintenance	Not applicable.
Compatibility	Compatible with most paint coating systems except cellulosic types. If in doubt conduct a test first.
Settlement	Stir well before use.
Shelf-life/Storage	Many years in original sealed container in a cool, dry place. Always replace lid and keep the container tightly closed.
Hazards	Flammable liquid and vapour. Do not inhale fumes. Keep away from ignition sources. Avoid skin and eye contact. Keep away from children. For full safety data sheet visit www.coatimshop.co.uk
Clean-Up	Brushes may be cleaned with white spirit immediately after use.
Sizes	500ml (BM80), 1 lt. (BM81), 2.5 lt.(BM82) tins.