

Walls sized with PEEL before decoration, provide a uniformly sealed surface ensuring firm adhesion, yet this unique coating enables the wall covering to be peeled from the wall dry without the need to soak, scrape or steam - an average room can be stripped in 8 minutes.

One application of PEEL Wallcovering-Release Coat will last for several decorations without renewing. PEEL can be used on any type of surface – plaster (painted or unpainted), timber, plywood, tiles, brick, glass, etc.

#### INSTRUCTIONS:

1. Wall surface must be smooth, clean, sound and completely dry.
2. Mix one and a half to two litres of cold water with contents and stir thoroughly.
3. Apply uniformly to the wall surface, brush well out and avoid going back over coated area.
4. The diluted mix will cover a wall area equivalent to approx 24 rolls of wallpaper (approx 125 sq mtrs).
5. Leave to dry one hour before hanging decoration.

The PEEL release system can successfully be used with wallpaper, vinyl wallcovering and hessian, etc. Wallcovering can be hung with any traditional paste system. Wash brushes in warm water.

*All recommendations and suggestions are made without guarantee since the conditions of use are beyond our control.*

**PROTECT FROM FROST**

**Contents 5 litres e**

For information on Brummer products visit our website at [www.brummer.co.uk](http://www.brummer.co.uk)  
or contact us at Brummer, Waterloo Road, London, NW2 7TX United Kingdom [sales@woodfillers.co.uk](mailto:sales@woodfillers.co.uk)  
Telephone: +44 (0)20 8450 4666