

**PRODUCT DATA SHEET**

<b>Product</b>	<b>ASAP Quick Dry All Surface All Purpose Paint for Barns &amp; Out-buildings</b>
<b>Type</b>	Rustins ASAP Quick Dry All Surface All Purpose Paint for Barns & Out-buildings is a high performance exterior quality acrylic satin paint available in black.
<b>Intended Use</b>	For use on a wide range of surfaces including most paints and varnishes and directly onto wood, MDF, metals including galvanised steel, industrial cladding, many common plastics, i.e. UPVC,, stonework and plaster without priming first.
<b>Special Features</b>	Rustins ASAP Quick Dry All Surface All Purpose Paint for Barns & Out-buildings is specially formulated to resist flaking or peeling due to its inherently flexible nature. Specifically designed for use on vertical surfaces.
<b>Preparation</b>	Essentially no primer is required before the paint is applied to surfaces. However all surfaces must be clean and free from any dirt, dust or grease and free from damp. Glossy areas need to be sanded lightly to allow the surface to be ready for application. If there is any flaking, remove it with a scrapper or with Rustins Strypit Paint and Varnish Remover. To enhance the application on metals an anti-corrosive primer such as Rustins Quick Dry Red Oxide or Galvanised Metal Primer can be first applied. The product may also be applied directly onto wood, but a suitable primer such as Rustins Quick Dry Primer and Undercoat will help reduce the appearance of visible wood grain if this is required. Test on a small inconspicuous area before painting the whole area.
<b>Application</b>	STIR WELL BEFORE USE. Do not thin the product. Apply evenly by brush. One or two coats should be applied allowing 3-4 hours between coats in warm, dry conditions, Cold, damp application conditions will significantly extend the drying time. Do not apply outdoors when very humid, foggy or when it is likely to rain before the paint has dried.
<b>Coats</b>	One coat is usually sufficient, but a second coat may be applied for extra durability.
<b>Drying Time</b>	Touch dry 30 minutes, depending on temperature and humidity.
<b>Re-coating Time</b>	Approx. 3-4 hours, depending on temperature and humidity
<b>Application Temp.</b>	Ideally 15-25°C. Do not apply below 10°C or if rain is imminent.
<b>Coverage</b>	Approx. 13 sq. metres per litre, depending on the absorbency of the surface.
<b>Maintenance</b>	The surface may be washed with a mild detergent solution and scrubbing brush and recoated if necessary.
<b>Compatibility</b>	Compatible with most paints and varnishes and directly onto wood, MDF, metals including galvanised steel, industrial cladding, many common plastics, i.e. UPVC, stonework and plaster without priming. If in doubt check compatibility and adhesion first.
<b>Settlement</b>	Stir well before and during use.
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in cool, dry place.
<b>Hazards</b>	Keep out of reach of children. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of water. Wear suitable protective clothing and gloves. Full Safety Data Sheet available from <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	Remove excess product from brushes before cleaning. Clean brushes whilst wet with water and mild detergent. Hard brushes may be cleaned with Rustins Brush Restorer.
<b>Sizes</b>	5 litres